



**Product:** [88240](#) 

50 Ohm Wireless Transmission Coax, RG-58, 20 AWG Solid BC, 95% TC Braid, FEP Jkt, CMP

### Product Description

50 Ohm Wireless Transmission Coax, RG-58, 20 AWG Solid Bare Copper Conductor , FEP Insulation, 95% Tinned Copper Braid Shield, FEP Jacket, CMP

### Technical Specifications

#### Product Overview

|                        |  |
|------------------------|--|
| Suitable Applications: | Point-to-point and point-to-multipoint wireless antenna communication; Wireless microphones, Two-Way Radios, Amateur (Ham) Radio, Low Power FM, GPS, RFID (Radio Frequency Identification) |
|------------------------|--|

#### Construction Details

|          |    |
|----------|----|
| RG Type: | 58 |
|----------|----|

#### Conductor

| Size   | Stranding | Nom. Diameter | Material         |
|--------|-----------|---------------|------------------|
| 20 AWG | Solid     | 0.032 in      | BC - Bare Copper |

#### Insulation

| Material                             | Nom. Insulation Diameter |
|--------------------------------------|--------------------------|
| FEP - Fluorinated Ethylene Propylene | 0.107 in (2.72 mm)       |

#### Outer Shield

| Outer Shield Type | Material           | Coverage |
|-------------------|--------------------|----------|
| Braid             | Tinned Copper (TC) | 95%      |

#### Outer Jacket

| Material                             | Nom. Diameter      |
|--------------------------------------|--------------------|
| FEP - Fluorinated Ethylene Propylene | 0.159 in (4.04 mm) |

|                                   |                    |
|-----------------------------------|--------------------|
| Overall Cable Diameter (Nominal): | 0.159 in (4.04 mm) |
|-----------------------------------|--------------------|

#### Electrical Characteristics

##### Attenuation

| Frequency | Nom. Attenuation |
|-----------|------------------|
| 1 MHz     | 0.5 dB/100ft     |
| 10 MHz    | 1.2 dB/100ft     |
| 50 MHz    | 3.0 dB/100ft     |
| 100 MHz   | 4.3 dB/100ft     |
| 200 MHz   | 6.4 dB/100ft     |
| 400 MHz   | 9.7 dB/100ft     |
| 700 MHz   | 13.7 dB/100ft    |
| 900 MHz   | 16.1 dB/100ft    |
| 1000 MHz  | 17.3 dB/100ft    |

##### Power Rating

| Frequency | Max. Power Rating |
|-----------|-------------------|
| 1 MHz     | 4,799 W           |

|           |         |
|-----------|---------|
| 10 MHz    | 1,937 W |
| 50 MHz    | 782 W   |
| 100 MHz   | 542 W   |
| 200 MHz   | 370 W   |
| 400 MHz   | 249 W   |
| 700 MHz   | 178 W   |
| 900 MHz   | 153 W   |
| 1,000 MHz | 143 W   |

#### Electricals

| Nom. Conductor DCR            | Nom. Outer Shield DCR      | Nom. Capacitance Cond-to-Shield | Nom. Characteristic Impedance | Nom. Velocity of Prop. |
|-------------------------------|----------------------------|---------------------------------|-------------------------------|------------------------|
| 10.1 Ohm/1000ft (33.1 Ohm/km) | 3.8 Ohm/1000ft (12 Ohm/km) | 27.4 pF/ft (89.9 pF/m)          | 53 Ohm                        | 70%                    |

#### Voltage

|                          |
|--------------------------|
| <b>UL Voltage Rating</b> |
| 300 V (CMP)              |

## Mechanical Characteristics

#### Temperature

| UL Temperature | Operating       |
|----------------|-----------------|
| 200°C          | -70°C to +200°C |

#### Bend Radius

|                          |
|--------------------------|
| <b>Installation Min.</b> |
| 1.6 in                   |

|                    |                |
|--------------------|----------------|
| Max. Pull Tension: | 39 lbs (18 kg) |
| Bulk Cable Weight: | 26 lbs/1000ft  |

## Standards and Compliance

|                                  |  |
|----------------------------------|--|
| Environmental Suitability:       | Indoor - Plenum, Indoor, Outdoor, UV Resistance  |
| Sustainability:                  | CA Prop 65   |
| Flammability / Reaction to Fire: | NFPA 262   |
| NEC / UL Compliance:             | CMP  |
| CEC / C(UL) Compliance:          | CMP  |
| European Directive Compliance:   | EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), REACH, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE) |
| APAC Compliance:                 | China RoHS II (GB/T 26572-2011)  |
| Non-Plenum Number:               | 8240   |

## History

|                      |  |
|----------------------|--|
| Update and Revision: | Revision Number: 0.357 Revision Date: 12-15-2021 |
|----------------------|--|

#### Variants

| Item #         | Color | Putup Type   | Length   | UPC          |
|----------------|-------|--------------|----------|--------------|
| 88240 010500   | Black | Reel         | 500 ft   | 612825434870 |
| 88240 0101000  | Black | Reel         | 1,000 ft | 612825216919 |
| 88240 010Z1000 | Black | ReelTuff Box | 1,000 ft | 612825216926 |

© 2022 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.