

DIN rail adapter - PTFIX 1,5-NS35 - 1049497

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

DIN rail adapter, length: 58.1 mm, width: 21.6 mm, height: 11 mm



Key Commercial Data

Packing unit	1 pc
Minimum order quantity	30 pc
GTIN	 4 055626 661513
GTIN	4055626661513
Weight per Piece (excluding packing)	4.000 g
Custom tariff number	39269097
Country of origin	Poland

Technical data

General

Ambient temperature (operation)	-60 °C ... 105 °C (max. short-term operating temperature 130°C)
Ambient temperature (storage/transport)	-25 °C ... 60 °C (for a short time, not exceeding 24h, -60°C to +70°C)
Permissible humidity (storage/transport)	30 % ... 70 %
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C

Dimensions

Width	21.6 mm
Length	58.1 mm
Height	11 mm

DIN rail adapter - PTFIX 1,5-NS35 - 1049497

Classifications

eCl@ss

eCl@ss 10.0.1	27370419
eCl@ss 11.0	27370419
eCl@ss 8.0	27370419
eCl@ss 9.0	27370419

ETIM

ETIM 5.0	EC001024
ETIM 6.0	EC001024
ETIM 7.0	EC001024

Approvals

Approvals


Approvals

EAC / CSA / cUL Recognized / UL Recognized / cULus Recognized

Ex Approvals


Approval details


EAC		RU C- DE.AI30.B.01102
-----	---	--------------------------


CSA		http://www.csagroup.org/services-industries/product-listing/	13631
	B	C	D
Nominal voltage UN	300 V	150 V	300 V
Nominal current IN	20 A	20 A	10 A
mm ² /AWG/kcmil	26-12	26-12	26-12

DIN rail adapter - PTFIX 1,5-NS35 - 1049497

Approvals

cUL Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 60425
	B	C	D
Nominal voltage UN	300 V	150 V	300 V
Nominal current IN	15 A	15 A	10 A
mm ² /AWG/kcmil	26-14	26-14	26-14

UL Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 60425
	B	C	D
Nominal voltage UN	300 V	150 V	300 V
Nominal current IN	20 A	20 A	10 A
mm ² /AWG/kcmil	26-12	26-12	26-12

cULus Recognized	
------------------	---