

# Cable - FLK 26/EZ-DR/ 200/KONFEK



2299411

<https://www.phoenixcontact.com/gb/products/2299411>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.

Round cable set; connection 1: IDC/FLK socket strip (1x 26-position); connection 2: IDC/FLK socket strip (1x 26-position); cable length: 2 m



## Your advantages

- Unshielded

## Commercial Data

Item number	2299411
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to Order (non-returnable)
Sales Key	CK2131
Product Key	CK2131
Catalog Page	Page 567 (C-5-2019)
GTIN	4017918886134
Weight per Piece (including packing)	210.2 g
Weight per Piece (excluding packing)	203 g
Customs tariff number	85444290
Country of origin	DE

## Technical Data

### Product properties

Product type	System cable
Insulation characteristics	
Overvoltage category	II
Pollution degree	2
Insulation	Functional insulation

### Environmental and real-life conditions

#### Ambient conditions

Degree of protection	IP00
Degree of protection Installation location	≥ IP54 (Installation location)
Ambient temperature (operation)	-40 °C ... 70 °C (fixed installation)
	-10 °C ... 70 °C (flexible installation)
Ambient temperature (storage/transport)	-40 °C ... 80 °C
Altitude	≤ 2000 m

### Electrical properties

Max. permissible operating voltage	25 V AC
	60 V DC
Nominal operating mode	100% operating factor
Max. current carrying capacity per path	1 A (50 °C)
	0.6 A (70 °C)
Rated insulation voltage	63 V
Rated surge voltage	0.6 kV

### Cable / line

Cable length	2 m
--------------	-----

#### 26X0.14 [PVC]

Number of positions	26
Shielded	no
Cable type	26X0.14 [PVC]
Conductor type	Round cable set
Conductor structure signal line	7x 0.16 mm
AWG signal line	26
Conductor cross section	26x 0.14 mm <sup>2</sup>
Wire diameter incl. insulation	1 mm ±0.03 mm
External cable diameter	8.3 mm ±0.4 mm
Outer sheath, material	Semi-rigid PVC
External sheath, color	gray
Conductor material	Tin-plated Cu litz wires

# Cable - FLK 26/EZ-DR/ 200/KONFEK



2299411

<https://www.phoenixcontact.com/gb/products/2299411>

Cable resistance	≤ 145 Ω/km (20 °C)
Insulation resistance	≥ 20 MΩ*km (20 °C)
Smallest bending radius, fixed installation	70 mm
Smallest bending radius, movable installation	131 mm
Max. bending cycles	5000 (at a radius of ≥ 15x outside diameter)
Halogen-free	no
Flame resistance	IEC 60332-1-2 (raw cable)
	VDE 0842, Part 332-1-2 (raw cable)
	IEC 60332-3-22 (raw cable)
	UL VW-1
	CSA FT-1
Resistance to oil	can withstand occasional splashes (raw cable)
Type	Cable for one module
Cable, preassembly	Insulation displacement, IEC 60352-4/DIN EN 60352-4

## color code

IDC/FLK26 (1)	IDC/FLK26 (1) = black
IDC/FLK26 (2)	IDC/FLK26 (2) = brown
IDC/FLK26 (3)	IDC/FLK26 (3) = red
IDC/FLK26 (4)	IDC/FLK26 (4) = orange
IDC/FLK26 (5)	IDC/FLK26 (5) = yellow
IDC/FLK26 (6)	IDC/FLK26 (6) = green
IDC/FLK26 (7)	IDC/FLK26 (7) = blue
IDC/FLK26 (8)	IDC/FLK26 (8) = violet
IDC/FLK26 (9)	IDC/FLK26 (9) = gray
IDC/FLK26 (10)	IDC/FLK26 (10) = white
IDC/FLK26 (11)	IDC/FLK26 (11) = white-black
IDC/FLK26 (12)	IDC/FLK26 (12) = white-brown
IDC/FLK26 (13)	IDC/FLK26 (13) = white-red
IDC/FLK26 (14)	IDC/FLK26 (14) = white-orange
IDC/FLK26 (15)	IDC/FLK26 (15) = white-yellow
IDC/FLK26 (16)	IDC/FLK26 (16) = white-green
IDC/FLK26 (17)	IDC/FLK26 (17) = white-blue
IDC/FLK26 (18)	IDC/FLK26 (18) = white-violet
IDC/FLK26 (19)	IDC/FLK26 (19) = white-gray
IDC/FLK26 (20)	IDC/FLK26 (20) = brown-black
IDC/FLK26 (21)	IDC/FLK26 (21) = brown-red
IDC/FLK26 (22)	IDC/FLK26 (22) = brown-orange
IDC/FLK26 (23)	IDC/FLK26 (23) = brown-yellow
IDC/FLK26 (24)	IDC/FLK26 (24) = brown-green
IDC/FLK26 (25)	IDC/FLK26 (25) = brown-blue
IDC/FLK26 (26)	IDC/FLK26 (26) = brown-violet

## Connection data

# Cable - FLK 26/EZ-DR/ 200/KONFEK



2299411

<https://www.phoenixcontact.com/gb/products/2299411>

## Field level

Connection in acc. with standard	IEC 60603-13
Connection method	IDC/FLK socket strip
Number of connections	1
Number of positions	26
Insertion/withdrawal cycles	> 50
Pitch	2.54 mm

## Controller level

Connection in acc. with standard	IEC 60603-13
Connection method	IDC/FLK socket strip
Number of connections	1
Number of positions	26
Insertion/withdrawal cycles	> 50
Pitch	2.54 mm


## Standards and regulations

### Air clearances and creepage distances

Standards/regulations	DIN EN 50178
-----------------------	--------------

## Drawings

Diagram



Maximum permissible current per path in uncoiled state

# Cable - FLK 26/EZ-DR/ 200/KONFEK



2299411

<https://www.phoenixcontact.com/gb/products/2299411>

## Approvals



### EAC

Approval ID: RU\*-DE.HB\*35.B00385



### UL Listed

Approval ID: FILE E 238705

	Nominal Voltage $U_N$	Nominal Current $I_N$	Cross Section AWG	Cross Section $\text{mm}^2$
	125 V	1 A	-	-



### cUL Listed

Approval ID: FILE E 238705

	Nominal Voltage $U_N$	Nominal Current $I_N$	Cross Section AWG	Cross Section $\text{mm}^2$
	125 V	1 A	-	-

### cULus Listed

# Cable - FLK 26/EZ-DR/ 200/KONFEK



2299411

<https://www.phoenixcontact.com/gb/products/2299411>

## Classifications

### ECLASS

ECLASS-9.0	27242220
ECLASS-10.0.1	27242220
ECLASS-11.0	27242220

### ETIM

ETIM 8.0	EC000237
----------	----------

### UNSPSC

UNSPSC 21.0	26121600
-------------	----------

# Cable - FLK 26/EZ-DR/ 200/KONFEK



2299411

<https://www.phoenixcontact.com/gb/products/2299411>

## Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

# Cable - FLK 26/EZ-DR/ 200/KONFEK

2299411

<https://www.phoenixcontact.com/gb/products/2299411>



## Accessories

### Cable marker carrier

Cable marker carrier - KME - 0807083

<https://www.phoenixcontact.com/gb/products/0807083>



Cable marker carrier, white, unlabeled, mounting type: Assembly with cable ties, cable diameter: > 5 mm, lettering field size: 20 mm x 8 mm

---

Phoenix Contact 2023 © - all rights reserved  
<https://www.phoenixcontact.com>

PHOENIX CONTACT Ltd  
Halesfield 13, Telford  
Shropshire, TF7 4PG  
01952 681700  
[info@phoenixcontact.co.uk](mailto:info@phoenixcontact.co.uk)