

# Cable - FLK 50/EZ-DR/D37SUB/ 50/Y81P-O



2302599

<https://www.phoenixcontact.com/pc/products/2302599>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Round cable set; controller: Mitsubishi Electric MELSEC Q (Y81P); connection 1: D-SUB socket strip (1x 37-position); connection 2: IDC/FLK socket strip (1x 50-position); cable length: 0.5 m

## Commercial Data

Item number	2302599
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to Order (non-returnable)
Product Key	CK2143
Catalog Page	Page 482 (C-5-2019)
GTIN	4017918910273
Weight per Piece (including packing)	233.9 g
Weight per Piece (excluding packing)	225.6 g
Customs tariff number	85444290
Country of origin	DE

## Technical Data

### Product properties

Product type	System cable
Insulation characteristics	
Overvoltage category	II
Pollution degree	2
Insulation	Functional insulation

### Environmental and real-life conditions

#### Ambient conditions

Degree of protection	IP00
Degree of protection Installation location	≥ IP54 (Installation location)
Ambient temperature (operation)	-40 °C ... 70 °C (fixed installation) -10 °C ... 70 °C (flexible installation)
Ambient temperature (storage/transport)	-40 °C ... 80 °C
Altitude	≤ 2000 m

### Electrical properties

Max. permissible operating voltage	25 V AC
	60 V DC
Nominal operating mode	100% operating factor
Max. current carrying capacity per path	1 A (50 °C)
	0.6 A (70 °C)
Rated insulation voltage	63 V
Rated surge voltage	0.6 kV

#### Supported controller MITSUBISHI MELSEC Q

Suitable I/O card	QY81P
-------------------	-------

### Cable / line

Cable length	0.5 m
--------------	-------

#### 50X0.14 [PVC]

UL AWM Style	2464/1061
Number of positions	50
Shielded	no
Cable type	50X0.14 [PVC]
Conductor type	Round cable set
Conductor structure signal line	7x 0.16 mm
AWG signal line	26
Conductor cross section	50x 0.14 mm <sup>2</sup>
Wire diameter incl. insulation	1 mm ±0.03 mm

# Cable - FLK 50/EZ-DR/D37SUB/ 50/Y81P-O



2302599

<https://www.phoenixcontact.com/pc/products/2302599>

External cable diameter	10.3 mm ±0.4 mm
Outer sheath, material	Semi-rigid PVC
External sheath, color	gray
Conductor material	Tin-plated Cu litz wires
Cable resistance	≤ 145 Ω/km (20 °C)
Insulation resistance	≥ 20 MΩ*km (20 °C)
Smallest bending radius, fixed installation	86 mm
Smallest bending radius, movable installation	161 mm
Max. bending cycles	5000 (at a radius of ≥ 15x outside diameter)
Halogen-free	no
Flame resistance	IEC 60332-1-2 (raw cable)
	VDE 0842, Part 332-1-2 (raw cable)
	IEC 60332-3-22 (raw cable)
	UL VW-1
	CSA FT-1
Resistance to oil	can withstand occasional splashes (raw cable)
Type	Cable for one module

## color code

D-SUB37 (17)	IDC/FLK50 (1) = black
D-SUB37 (18)	IDC/FLK50 (2) = brown
D-SUB37 (1)	IDC/FLK50 (3) = red
D-SUB37 (20)	IDC/FLK50 (4) = orange
D-SUB37 (2)	IDC/FLK50 (5) = yellow
D-SUB37 (21)	IDC/FLK50 (6) = green
D-SUB37 (3)	IDC/FLK50 (7) = blue
D-SUB37 (22)	IDC/FLK50 (8) = violet
D-SUB37 (4)	IDC/FLK50 (9) = gray
D-SUB37 (23)	IDC/FLK50 (10) = white
D-SUB37 (19)	IDC/FLK50 (11) = white-black
D-SUB37 (37)	IDC/FLK50 (12) = white-brown
D-SUB37 (17)	IDC/FLK50 (13) = white-red
D-SUB37 (18)	IDC/FLK50 (14) = white-orange
D-SUB37 (5)	IDC/FLK50 (15) = white-yellow
D-SUB37 (24)	IDC/FLK50 (16) = white-green
D-SUB37 (6)	IDC/FLK50 (17) = white-blue
D-SUB37 (25)	IDC/FLK50 (18) = white-violet
D-SUB37 (7)	IDC/FLK50 (19) = white-gray
D-SUB37 (26)	IDC/FLK50 (20) = brown-black
D-SUB37 (8)	IDC/FLK50 (21) = brown-red
D-SUB37 (27)	IDC/FLK50 (22) = brown-orange
D-SUB37 (19)	IDC/FLK50 (23) = brown-yellow
D-SUB37 (37)	IDC/FLK50 (24) = brown-green
D-SUB37 (17)	IDC/FLK50 (25) = brown-blue

# Cable - FLK 50/EZ-DR/D37SUB/ 50/Y81P-O



2302599

<https://www.phoenixcontact.com/pc/products/2302599>

D-SUB37 (36)	IDC/FLK50 (26) = brown-violet
D-SUB37 (9)	IDC/FLK50 (27) = brown-gray
D-SUB37 (28)	IDC/FLK50 (28) = brown-white
D-SUB37 (10)	IDC/FLK50 (29) = green-black
D-SUB37 (29)	IDC/FLK50 (30) = green-brown
D-SUB37 (11)	IDC/FLK50 (31) = green-red
D-SUB37 (30)	IDC/FLK50 (32) = green-orange
D-SUB37 (12)	IDC/FLK50 (33) = green-blue
D-SUB37 (31)	IDC/FLK50 (34) = green-violet
D-SUB37 (19)	IDC/FLK50 (35) = green-gray
D-SUB37 (37)	IDC/FLK50 (36) = green-white
D-SUB37 (36)	IDC/FLK50 (37) = yellow-black
D-SUB37 (18)	IDC/FLK50 (38) = yellow-brown
D-SUB37 (13)	IDC/FLK50 (39) = yellow-red
D-SUB37 (32)	IDC/FLK50 (40) = yellow-orange
D-SUB37 (14)	IDC/FLK50 (41) = yellow-blue
D-SUB37 (33)	IDC/FLK50 (42) = yellow-violet
D-SUB37 (15)	IDC/FLK50 (43) = yellow-gray
D-SUB37 (34)	IDC/FLK50 (44) = yellow-white
D-SUB37 (16)	IDC/FLK50 (45) = gray-black
D-SUB37 (35)	IDC/FLK50 (46) = gray-brown
D-SUB37 (19)	IDC/FLK50 (47) = gray-red
D-SUB37 (37)	IDC/FLK50 (48) = gray-orange

## Connection data

### Field level

Connection in acc. with standard	IEC 60603-13
Connection method	IDC/FLK socket strip
Number of connections	1
Number of positions	50
Insertion/withdrawal cycles	> 50
Pitch	2.54 mm

### Controller level

Connection in acc. with standard	IEC 60807-2 DIN 41652
Connection method	D-SUB socket strip
Screw thread	M2,5
Number of connections	1
Number of positions	37
Tightening torque	0.2 Nm
Insertion/withdrawal cycles	> 200

## Standards and regulations

# Cable - FLK 50/EZ-DR/D37SUB/ 50/Y81P-O

2302599

<https://www.phoenixcontact.com/pc/products/2302599>




## Air clearances and creepage distances

Standards/regulations

DIN EN 50178

Drawings

Diagram



Maximum permissible current per path in uncoiled state

# Cable - FLK 50/EZ-DR/D37SUB/ 50/Y81P-O



2302599

<https://www.phoenixcontact.com/pc/products/2302599>

## Approvals



### EAC

Approval ID: RU\*-DE.HB\*35.B00385



### UL Listed

Approval ID: FILE E 238705

	Nominal Voltage $U_N$	Nominal Current $I_N$	Cross Section AWG	Cross Section $\text{mm}^2$
	125 V	1 A	-	-



### cUL Listed

Approval ID: FILE E 238705

	Nominal Voltage $U_N$	Nominal Current $I_N$	Cross Section AWG	Cross Section $\text{mm}^2$
	125 V	1 A	-	-

### cULus Listed

# Cable - FLK 50/EZ-DR/D37SUB/ 50/Y81P-O



2302599

<https://www.phoenixcontact.com/pc/products/2302599>

## Classifications

### ECLASS

ECLASS-9.0	27242220
ECLASS-10.0.1	27242220
ECLASS-11.0	27242220

### ETIM

ETIM 8.0	EC000237
----------	----------

### UNSPSC

UNSPSC 21.0	26121600
-------------	----------

# Cable - FLK 50/EZ-DR/D37SUB/ 50/Y81P-O



2302599

<https://www.phoenixcontact.com/pc/products/2302599>

## Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

# Cable - FLK 50/EZ-DR/D37SUB/ 50/Y81P-O

2302599

<https://www.phoenixcontact.com/pc/products/2302599>



## Accessories

### Cable marker carrier

Cable marker carrier - KME - 0807083

<https://www.phoenixcontact.com/pc/products/0807083>



Cable marker carrier, white, unlabeled, mounting type: Assembly with cable ties, cable diameter: > 5 mm, lettering field size: 20 mm x 8 mm

---

Phoenix Contact 2023 © - all rights reserved  
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachmarktstraße 8  
D-32825 Blomberg  
+49 (0) 5235-3 00  
[info@phoenixcontact.com](mailto:info@phoenixcontact.com)