

# S202U-K6

[Print View..](#)

## General Information

|                               |                 |
|-------------------------------|-----------------|
| <b>Extended Product Type:</b> | S202U-K6        |
| <b>Product ID:</b>            | 2CDS272417R0377 |
| <b>EAN:</b>                   | 4016779619561   |

### Catalog Description:

Miniature Circuit Breakers MCBs - S200U - Number of Poles 2 - Tripping characteristic K - Rated Current 6.00 A

### Long Description:

System pro M compact S200U miniature circuit breakers are current limiting. They have two different tripping mechanisms, the delayed thermal tripping mechanism for overload protection and the electromechanic tripping mechanism for short circuit protection. They are available in different characteristics (K,Z), configurations (1P,2P,3P,4P), breaking capacities (up to 10 kA) and rated currents (up to 63A). All MCBs of the product range S200U comply with IEC/EN 609 47-2, UL489 and CSA 22.2 No. 5, allowing the use for commercial and industrial applications.

No image available

## Categories

Products » Low Voltage Products and Systems » Modular DIN Rail Products » Miniature Circuit Breakers MCBs

## Ordering

|                                |                 |
|--------------------------------|-----------------|
| <b>Extended Product Type:</b>  | S202U-K6        |
| <b>Product ID:</b>             | 2CDS272417R0377 |
| <b>EAN:</b>                    | 4016779619561   |
| <b>Minimum Order Quantity:</b> | 1 piece         |
| <b>Country of Origin:</b>      | Germany (DE)    |

## Dimensions

|                            |          |
|----------------------------|----------|
| <b>Product Net Width:</b>  | 35.0 mm  |
| <b>Product Net Height:</b> | 92.0 mm  |
| <b>Product Net Length:</b> | 71.0 mm  |
| <b>Product Net Depth:</b>  | 71.0 mm  |
| <b>Product Net Weight:</b> | 0.280 kg |

## Container Information

|                                      |          |
|--------------------------------------|----------|
| <b>Package Level 1 Width:</b>        | 105.0 mm |
| <b>Package Level 1 Length:</b>       | 183.0 mm |
| <b>Package Level 1 Height:</b>       | 80.0 mm  |
| <b>Package Level 1 Gross Weight:</b> | 1.460 kg |
| <b>Package Level 1 Units:</b>        | 5 piece  |

## Technical


|   |              |
|---|--------------|
| <b>Number of Poles:</b>                               | 2            |
| <b>Tripping Characteristic:</b>                       | K            |
| <b>Rated Current (I<sub>n</sub>):</b>                 | 6.00 A       |
| <b>Rated Voltage (U<sub>r</sub>):</b>                 | 200 volts AC |
| <b>Rated Short-Circuit Capacity (I<sub>cn</sub>):</b> | 10.0 kA      |


## Environmental

|                     |   |
|---------------------|---|
| <b>RoHS Status:</b> | Following EU Directive 2002/95/EC August 18, 2005 and amendment |
|---------------------|---|

## Certificates and Declarations (Document Number)

News only 

☆ Rate this page 

↶ Share this page 



### Your preferences:

Egypt 

English 

**Declaration of Conformity - CE:** [2CDK403004D0401](#)

**RoHS Information:** [2CDK400003K0201](#)

---