


## 5749268-1 Product Details

### Have a Question?

Chat with a Product Information Specialist



**5749268-1**

TE Internal Number: 5749268-1

Active

### Shielded Miniature Circular DIN Connectors

Always EU RoHS/ELV Compliant (Statement of Compliance)

#### Product Highlights:

- Connector
- Mini DIN Connector Configuration
- 8 Positions
- PCB Mount Angle = Right Angle
- Shielded

[View all Features](#)

### Quick Links

- ▶ [Check Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

[Add to My Part List](#) [Request Sample](#) [Find Similar Products](#) [Buy Product](#)

### Documentation & Additional Information

Documents are temporarily unavailable. We are working hard to correct the problem. Please try again later.

#### Additional Information:

- [Product Line Information](#)

#### Related Products:

- [Tooling](#)

### Product Features (Please use the Product Drawing for all design activity)

#### Product Type Features:

- [Product Type](#) = Connector
- [PCB Mount Angle](#) = Right Angle
- [Front Panel Grounding](#) = Without
- [PCB Mount Retention](#) = Without
- [Gender](#) = Receptacle
- [Stacked](#) = No
- [Color Code](#) = None
- PCB Mount Style = Through Hole
- Shield Material = Copper Alloy

#### Electrical Characteristics:

- [Shielded](#) = Yes

#### Termination Related Features:

- [Grounding Clips](#) = Without
- Solder Tail Contact Plating = Tin

#### Body Related Features:

- Connector Configuration = Mini DIN
- [Number of Positions](#) = 8
- Shield Plating = Tin over Nickel

#### Contact Related Features:

- [Contact Plating, Mating Area, Material](#) = Gold Flash
- Contact Base Material = Copper Alloy
- Contact Underplating = Nickel

#### Housing Related Features:

- Housing Material = Thermoplastic - GF
- UL Flammability Rating = UL 94V-0
- Housing Color = Black

#### Configuration Related Features:

- SPDIF Connector = Without

#### Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Always was RoHS compliant

#### Other:

- Brand = AMP

BOOKMARK

### Corporate Information

[Who We Are](#)  
[Investors](#)  
[News Room](#)  
[Supplier Portal](#)  
[Careers](#)

### Quick Links

[Check Distributor Inventory](#)  
[Cross Reference](#)  
[Find Documents & Drawings](#)  
[Product Compliance Support Center](#)  
[Site Map](#)

### Customer Support

[Email or Chat with Us](#)  
[Find a Phone Number](#)  
[Search Knowledge Base](#)  
[Manage Your Account](#)

### Sign up for our eNewsletter

Enter your email address

Follow us on: