



+ CONNECTORS

DISCRETE SOCKETS



✓ Active

TE CONNECTIVITY (TE)

SOCKET,MIN-SPR B-N SN-AU SER-2

MINI-SPRING SOCKETS | Series 3

1-5645955-2

TE Internal Number: 1-5645955-2

EU RoHS Compliant

EU ELV Compliant

Hole Size (Recommended) 1.32 mm [.052 in]

Socket Length 4.67 mm [.184 in]

Sealant With

Sleeve Style Bullet Nose

Wire/Cable Size .081 – .326 mm² [28 – 22 AWG]

[↓](#) **PRODUCT DRAWING**
English

[↓](#) **3D PDF**

DOCUMENTATION

Product Drawings

MINIATURE SPRING SOCKET ASSY SERIES 2 LONG WITH SEALANT

PDF

English

CAD Files

Customer View Model

2D_DXF.ZIP

English

3D PDF

PDF

3D

Customer View Model

3D_IGS.ZIP

English

Customer View Model

3D_STP.ZIP

English

Product Environmental Compliance

TE Material Declaration

MD_1-5645955-2_072920151216_dmtec

PDF

English

FEATURES



Please review product documents or [contact us](#) for the latest agency approval information.

Please Note: Use the Product Drawing for all design activity.

Product Type Features

Sleeve Style Bullet Nose

Connector System Cable-to-Board

Sealable No

Connector & Contact Terminates To Printed Circuit Board

Product Type Contact

Profile Zero

Wire/Cable Type Discrete Wire

Body Features

Sealant With

Sleeve Plating Material Tin

Sleeve Material Copper

Contact Features

Contact Current Rating (Max) (A) 5

Contact Type Socket

Contact Spring Plating Thickness .762 μm [30 μin]

Contact Spring Plating Material Gold

Contact Mating Area Plating Thickness 30 μm [30 μin]

Contact Transmits (Typical) Signal (Data)/Power

Contact Base Material Beryllium Copper

Socket Type Discrete

Termination Features

Termination Method to PC Board Through Hole - Press-Fit

Termination Method to Wire/Cable Solder

Insertion Method Hand/Semi-Automatic/Automatic

Dimensions

Socket Length 4.67 mm [.184 in]

Hole Size (Recommended) 1.32 mm [.052 in]

Wire/Cable Size .081 – .326 mm² [28 – 22 AWG]

Mating Pin Diameter Range .36 – .66 mm [.014 – .026 in]

PCB Thickness (Recommended) .79 – 3.18 mm [.031 – .125 in]

Usage Conditions

Operating Temperature Range -65 – 125 °C [-85 – 257 °F]

Operation/Application

Circuit Application Power, Signal

Packaging Features

Packaging Method Reel

Packaging Quantity 10000

Other

Spring Material Beryllium Copper

PRODUCT COMPLIANCE



Statement of Compliance

Statement of Compliance

PDF
