

 Live Product Chat US Only
8:30am - 5pm ET, Mon - Fri



 Active

Always EU RoHS/ELV Compliant (Statement of Compliance)

- Receptacle
- Tab Fit = 6.35 x 0.81 mm
- Line = Mark I
- Receptacle Style = Straight
- Wire Range = 0.50-2.00² [20-14] mm [AWG]

[View all Features](#) | [Find Similar Products](#)

[Check Pricing & Availability](#)
[Search for Tooling](#)
[Product Feature Selector](#)
[Contact Us About This Product](#)

Product Drawings:

- [250 SERIES POSITIVE LOCK RECEPTACLE](#) (PDF, English)

Catalog Pages/Data Sheets:

- None Available

Product Specifications:

- [1-Position, Positive Lock Connector](#) (PDF, English)
- [JAPANESEE](#) (PDF, English)
- [1 POSITION POSITIVE LOCK CONNECTOR](#) (PDF, English)
- [No title \(1\)](#) (PDF, English)
- [No title \(2\)](#) (PDF, English)

Application Specifications:

- [Crimping of Positive Lock Receptacle Contact](#) (PDF, English)

Instruction Sheets:

- None Available

CAD Files: ([CAD Format & Compression Information](#))

- 2D Drawing (DXF, Version F)
- 3D Model (IGES, Version F)
- 3D Model (STEP, Version F)

List all Documents

Additional Information:

- Product Line Information

Related Products:

- Tooling

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Product Type = Receptacle
- Tab Fit (mm [in]) = 6.35 x 0.81 [.250 x .032]
- Receptacle Style = Straight
- Insulation Diameter (mm [in]) = 2.20-3.10
[.086-.122]
- Material = Brass
- Finish = Tin
- Keyed = No

Body Related Features:

- Wire Range (mm [AWG]) = 0.50-2.00² [20-14]
- Position Keyed = None
- Stock Thickness (mm [in]) = 0.38 [0.015]

Industry Standards:

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant

Packaging Related Features:

- Packaging Method = Strip

Other:

- Line = Mark I
- Brand = AMP