

MSP103C004 Product Details



MSP103C004
(1825516-3)

TE Internal Number: 1825516-3

 [Active](#)

Pushbutton Switches

 [Always EU RoHS/ELV Compliant \(Statement of Compliance\)](#)

Product Highlights:

- Switch
- Not Tactile
- Single Pole - Single Throw Configuration (Pole-Throw)
- Contact Rating = 3A
- Operating Function = Normally Open, Momentary

[View all Features](#)

Quick Links

- ▶ [Check Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

 [Add to My Part List](#)  [Request Sample](#)  [Find Similar Products](#)  [Buy Product](#)

Documentation & Additional Information

Product Drawings:

- [SWITCH, PUSHBUTTON MSP103, SILVER](#) (PDF, English)

Catalog Pages/Data Sheets:

- None Available

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files:

- None Available

Related Products:

- [Tooling](#)

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Product Type = Switch
- Tactile = No
- Configuration (Pole-Throw) = Single Pole - Single Throw
- [Series](#) = MSP3
- Mount Angle = Vertical
- Termination Type = Wire Lugs
- Actuator Style = Round

Electrical Characteristics:

- Contact Rating = 3A

Body Features:

- Mount Style = Panel
- Actuator Length (mm [in]) = 2.50 [0.098]
- Actuator Profile = Extended
- Actuator Color = Black
- Bushing Diameter = 1/4-40
- Case Material = Thermoplastic (LCP)
- Actuator Material = Thermoplastic

Contact Features:

- Contact Plating = Silver
- Contact Base Material = Copper Alloy

Housing Features:

- Process Sealed = No
- Low Profile = No
- Bushing Style = Threaded

Configuration Features:

- Operating Function = Normally Open, Momentary
- Ganged = No
- ESD Grounding Terminal = Without
- Number of Actuators = Single
- Illuminated = No
- Dust Proof = No
- Support Bracket = Without
- Snap Action = Without
- Bushing Length (mm [in]) = 5.97 [0.235]

Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Hand solderable with lead free solder
- RoHS/ELV Compliance History = Always was RoHS compliant

Conditions for Usage:

- Temperature Rating = Standard

Packaging Features:

- Packaging Method = Loose Piece

Other:

- Brand = Alcoswitch

Corporate Information

[Who We Are](#)
[Investors](#)
[News Room](#)
[Supplier Portal](#)
[Careers](#)

Quick Links

[Check Distributor Inventory](#)
[Cross Reference](#)
[Find Documents & Drawings](#)
[Product Compliance Support Center](#)
[Site Map](#)

Customer Support

[Email or Chat With Us](#)
[Find a Phone Number](#)
[Search Knowledge Base](#)
[Manage your Account](#)

Keep Me Informed

Receive TE News, Events & Technology Updates

Enter your email address

