


 Live Product Chat US Only
8:30am - 5pm ET, Mon - Fri



 Active

Always EU RoHS/ELV Compliant (Statement of Compliance)

? Mating Type = Plug
 ? Number of Positions = 32
 ? PCB Mount Angle = Right Angle
 ? Post Type = Solder Post
 ? Not Make First / Break Last

[View all Features](#) | [Find Similar Products](#)

[Check Pricing & Availability](#)
[Search for Tooling](#)
[View Mating Products \(7\)](#)
[Product Feature Selector](#)
[Contact Us About This Product](#)

Product Drawings:

- [ASSEMBLY, PIN, EUROCARD, TYPE 1/2B, 32 POSITION, 2.6...](#)
(PDF, English)

? None Available

? None Available

[Eurocard Connectors Types B,C,M,Q,R, & Enhanced Typ... \(PDF, English\)](#)

? None Available

? None Available

? Product Line Information

? Tooling

? Mating Products (7)

List all Documents

Product Type Features:

- ? Mating Type = Plug
 ? Number of Positions = 32
 ? PCB Mount Angle = Right Angle
 ? Post Type = Solder Post
 ? Make First / Break Last = No
 ? DIN Level = II
 ? Size = Half
 ? PCB Retention Feature = No
 ? Color = Gray
 ? Comment = Contact Finish: DIN 41612 Class 2
 In Contact Area.
 Tin On Posts.

? Termination (Solder) Post Length (mm [in]) = 2.65 [0.104]

? Contact Cross Section (mm [in]) = 0.64 [.025]
Sq.
? Rows Loaded = A, B

? Contact Material = Copper Alloy

?	Housing Material = Polymer	
?	Housing Flammability Rating = UL 94V	-0

- ? RoHS/ELV Compliance = RoHS compliant, ELV compliant
- ? Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- ? Flux - Tight Coating = Without
- ? RoHS/ELV Compliance History = Always was RoHS compliant

? Terminate To = Printed Circuit Board

? Brand = AMP