




**CONNECTORS**

**STANDARD RECTANGULAR CONNECTORS**



✓ Active

TE CONNECTIVITY (TE)

## RITS CONN.SOCKET ASSY 3P BLUE

RITS | RITS Socket Connectors

2-1746741-3

TE Internal Number: 2-1746741-3

EU RoHS Compliant

EU ELV Compliant

**Product Type** Connector

**Connector Style** Receptacle

**Mating Alignment** With

**Mating Alignment Type** Polarization

**Mating Retention** With

[↓ PRODUCT DRAWING](#)  
English

[↓ 3D PDF](#)

### DOCUMENTATION

Product Drawings

#### **SOCKET ASSY RITS CONN**

PDF (TIFF AVAILABLE)

**English**

CAD Files

#### **3D PDF**

PDF

**3D**

#### **Customer View Model**

2D\_DXF.ZIP

**English**

### **Customer View Model**

3D\_IGS.ZIP

**English**

### **Customer View Model**

3D\_STP.ZIP

**English**

---

Product Specifications

Product Specification

### **RITS CONNECTOR**

TIF

**Japanese**

### **RITS CONNECTOR**

PDF

**Japanese**

---

Instruction Sheets

Instruction Sheet (non U.S.)

### **RITS Connector Interconnection System/E-CON Connector**

PDF

**Japanese**

### **RITS Connector Interconnection System/E-CON Connector**

TIF

**Japanese**

### **HAND TOOL FOR RITS PLUG SOCKET ASSEMBLY**

PDF

**Japanese**

### **HAND TOOL FOR RITS PLUG SOCKET ASSEMBLY**

TIF

**Japanese**

---

## **FEATURES**



Please review product documents or [contact us](#) for the latest agency approval information.

Please Note: Use the Product Drawing for all design activity.

---

Product Type Features

**Shrouded** No  
**Product Type** Connector  
**Connector Style** Receptacle  
**Connector System** Wire-to-Board  
**Shielded** No  
**Sealable** No  
**Connector & Contact Terminates To** Printed Circuit Board  
**Connector Type** Connector Assembly  
**Glow Wire Rating** Standard Part - Not Glow Wire

---

#### Configuration Features

**Selectively Loaded** No  
**Number of Positions** 3  
**Number of Rows** 1  
**Preloaded** Yes

---

#### Electrical Characteristics

**Operating Voltage (VDC)** 32

---

#### Contact Features

**Contact Plating Material** Gold Over Nickel  
**Contact Current Rating (Max) (A)** 3  
**Shunts/Shorting Bars** Without  
**Contact Layout** Inline  
**Multiple Contact Types** Without  
**Contact Type** Socket

---

#### Termination Features

**Termination Method to Wire/Cable** Crimp

---

#### Mechanical Attachment

**Panel Mount** No  
**PCB Mount Alignment** Without  
**Mating Alignment** With  
**Mating Alignment Type** Polarization  
**Mating Retention** With  
**Mating Retention Type** Latch  
**PCB Mount Retention** Without  
**Contact Retention** Without

---

#### Housing Features

**Centerline (Pitch) (in)** .079  
**Housing Material** Thermoplastic GF  
**Housing Color** Blue

---

#### Dimensions

**Length** 13.8 mm [.543 in]  
**Height** 23 mm [.905 in]  
**Width** 8.6 mm [.338 in]

---

#### Usage Conditions

**Operating Temperature Range** -30 – 75 °C [-22 – 167 °F]

---

Operation/Application

**Halogen Free** Yes

**For Use With** Header

**Assembly Integration Feature** Without

---

Identification Marking

**Circuit Identification Feature** Without

---

Industry Standards

**UL Flammability Rating** UL 94V-0

---

Packaging Features

**Packaging Method** Tube

**Packaging Quantity** 34

---

## PRODUCT COMPLIANCE



Statement of Compliance

**Statement of Compliance**

PDF

---