



Technical Data



- Max. 250mA/120V/9W AC/6W DC
- 2 pole
- momentary or alternate
- 8 contact functions
- temperature range:
 - low temp: -40/+75°C
 - high temp: -40/+160°C
- through-hole version





Dimensions





PCB layout





Dimensions (w/LED)





PCB layout (top view)







Dimensions (w/2 LEDs)









PCB layout (top view)



How to order

	1 5	+	1 6 2 7 0	+	1 6 3 0 0	+	1 6 3 2 4	
Switch			Extender		Cap		Bezel	
15501 mom. silver								
15551 alt. silver					00 blue	30 ultra blue	01 brown	
15502 mom. gold					01 brown	40 dusty blue	03 grey	
15552 alt. gold					02 green	42 aqua blue	06 white	
15500 silent silver					03 grey	32 mint green	09 black	
15401 mom. silver high temp.					04 yellow	33 tele grey		
15402 mom. gold high temp.					05 golden	34 melon		
15420 silent gold high temp.					06 white	38 noble red		
15451 alt. silver high temp.					07 orange	50 metal dark blue		
					08 red	53 metal light grey		
					09 black	57 metal dark grey		
						58 metal bordeaux		

	1 5	+	1 6 2 7 0	+	1 6 3 0 0	+	1 6 3 2 7	+	1 6 9 2 2
Switch			Extender		Cap		16325		LED
									
							16326		
									
							Lens 16327		LED 16922
							02 green		02 green
							04 yellow		04 yellow
							08 red		08 red
							2 required		2 required

Ordering example: 15501 + 16270 + 1630008 + 1632509 + 1632708 + 1692208

For updates of products and/or changes of specifications please see www.mec.dk