




Industrial grade straight blade receptacles

Product description


2-pole, 3-wire grounding
 15A, 250V/AC
 20A, 250V/AC
 NEMA 6-15R, 6-20R




60W48



60W49DPLX



AH5684



834B

Watertight special use industrial grade receptacles

Rating	A	V/AC	NEMA	Description	Color	Catalog no.	
15 250 6-15R				Single watertight receptacle, back wire	Y	□ 60W49	
				Single watertight receptacle, back wire	BK	□ 60W49BK	
				Duplex watertight receptacle, back wire	Y	□ 60W49DPLX	
				Duplex watertight receptacle, back wire	BK	□ 60W49DPLXBK	
20 250 6-20R				Single watertight receptacle, back wire	Y	□ 60W48	
				Single watertight receptacle, back wire	BK	□ 60W48BK	
				Duplex watertight receptacle, back wire	Y	□ 60W48DPLX	
				Duplex watertight receptacle, back wire	BK	□ 60W48DPLXBK	

NOTE: See Complex Environments (Section D) for more information


Special use panel-mount industrial single receptacles

Rating	A	V/AC	NEMA	Description	Color	Catalog no.			
15 250 6-15R				Strap center to center spacing 1.9375" (49.2mm), back & side wire, short strap	B	□ AH5684			

Industrial grade straight blade receptacles

Product description

2-pole, 3-wire grounding
 15A, 277V/AC
 20A, 277V/AC
 NEMA 7-15R, 7-20R



Industrial grade receptacles

Rating	A	V/AC	NEMA	Description	Color	Catalog no.		
15 277 7-15R				Duplex receptacle, back & side wire	B	□ 5302B [†]		
20 277 7-20R				Single receptacle, side wire only	B	□ 834B		

[†] UL only

Color information:

B (Brown), BK (Black), Y (Yellow)



Specification information: Panel mount industrial receptacles: A-31, Industrial receptacles: A-35, Watertight industrial receptacles: A-35

Compliances, specifications and availability are subject to change without notice.

Indicates NAFTA compliant - Page Q-32

RoHS compliant - Page Q-32