

PermaSleeve® PS Wire Marking Sleeves (B-342)

These heat-shrink sleeves are the ultimate in marker durability, permanence and aesthetic appearance. Fast shrink rate saves time and costs during installation. Military / Industrial grade 3:1 shrink ratio. Meets several MIL, SAE and ASTM specs. Available as individual die-cut or continuous cut-to-length tubing.




Figure 44




Figure 58



Fits Printer Model	Diagram	Catalog #	B#	Color	Approx. Wire Gauge	For Wire Diameter Inch (mm) Min. Max	Sleeve Width A Inch (mm)	Supplied Diameter B Inch (mm)	Sleeves/ Roll	Ribbon in Cartridge
B-342 – PermaSleeve® PS Wire Marking Sleeve										
BMP41, 51, 53	Fig. 44	M-125-075-342	B-342	BK on WT	22-16 Gauge	0.046 - 0.110 (1.20 - 2.80 mm)	0.750 (19.1)	0.235 (5.97)	80	R4300
BMP51, 53	Fig. 44	M-125-1-342	B-342	BK on WT	22-16 Gauge	0.046 - 0.110 (1.20 - 2.80 mm)	1.000 (25.40)	0.235 (5.97)	80	R4300
BMP41, 51, 53	Fig. 44	M-187-075-342	B-342	BK on WT	20-10 Gauge	0.062 - 0.150 (1.60 - 3.80 mm)	0.750 (19.1)	0.335 (8.51)	80	R4300
BMP51, 53	Fig. 44	M-187-1-342	B-342	BK on WT	20-10 Gauge	0.062 - 0.150 (1.60 - 3.80 mm)	1.000 (25.40)	0.335 (8.51)	80	R4300
BMP41, 51, 53	Fig. 44	M-250-075-342	B-342	BK on WT	16-8 Gauge	0.094 - 0.215 (2.40 - 5.50 mm)	0.750 (19.1)	0.439 (11.15)	80	R4300
BMP51, 53	Fig. 44	M-250-1-342	B-342	BK on WT	16-8 Gauge	0.094 - 0.215 (2.40 - 5.50 mm)	1.000 (25.40)	0.439 (11.15)	80	R4300
BMP41, 51, 53	Fig. 44	M-375-075-342	B-342	BK on WT	12-4 Gauge	0.125 - 0.320 (3.20 - 8.10 mm)	0.750 (19.1)	0.645 (16.38)	80	R4300
BMP51, 53	Fig. 44	M-375-1-342	B-342	BK on WT	12-4 Gauge	0.125 - 0.320 (3.20 - 8.10 mm)	1.000 (25.40)	0.645 (16.38)	80	R4300
B-342 – PermaSleeve® PS Continuous Sleeving										
BMP41, 51, 53	Fig. 58	MC-125-342	B-342	BK on WT	22-16 Gauge	0.046 - 0.110 (1.20 - 2.80 mm)	7 ft (2.13 m)	0.235 (5.97)	1 roll (cont.)	R4300
BMP41, 51, 53	Fig. 58	MC-125-342-YL	B-342	BK on YL	22-16 Gauge	0.046 - 0.110 (1.20 - 2.80 mm)	7 ft (2.13 m)	0.235 (5.97)	1 roll (cont.)	R4300
BMP41, 51, 53	Fig. 58	MC-187-342	B-342	BK on WT	20-10 Gauge	0.062 - 0.150 (1.60 - 3.80 mm)	7 ft (2.13 m)	0.335 (8.51)	1 roll (cont.)	R4300
BMP41, 51, 53	Fig. 58	MC-187-342-YL	B-342	BK on YL	20-10 Gauge	0.062 - 0.150 (1.60 - 3.80 mm)	7 ft (2.13 m)	0.335 (8.51)	1 roll (cont.)	R4300
BMP41, 51, 53	Fig. 58	MC-250-342	B-342	BK on WT	16-8 Gauge	0.094 - 0.215 (2.40 - 5.50 mm)	7 ft (2.13 m)	0.439 (11.15)	1 roll (cont.)	R4300
BMP41, 51, 53	Fig. 58	MC-250-342-YL	B-342	BK on YL	16-8 Gauge	0.094 - 0.215 (2.40 - 5.50 mm)	7 ft (2.13 m)	0.439 (11.15)	1 roll (cont.)	R4300
BMP41, 51, 53	Fig. 58	MC1-375-342	B-342	BK on WT	12-4 Gauge	0.125 - 0.320 (3.20 - 8.10 mm)	7 ft (2.13 m)	0.645 (16.38)	1 roll (cont.)	R4300

* Approximate wire gauge based on AWG for THHN wire.

Wire & Cable Flags and Tags (B-109, B-145, B-425, B-499)

Allow more legible information on data cables and smaller diameter wires. Permits you to handle and view labels without touching the wires.




Figure 48




Figure 50




Figure 57




Figure 63



Fits Printer Model	Diagram	Catalog #	B#	Material	Color	Label Width A Inch (mm)	Label Height B Inch (mm)	Label Height C Inch (mm)	Labels/ Roll	Ribbon in Cartridge
B-109 – Polypropylene Tag										
BMP51, 53	Fig. 57	M-12-109	B-109	Polypropylene Tag	BK on WT	3.000 (76.2)	0.750 (19.05)	-	80	R4300
B-145 – Polypropylene Tag										
BMP51, 53	Fig. 50	M-111-145FR-GY	B-145	Polyethylene Tag	BK on GY	1.206 (30.63)	0.750 (19.05)	-	80	R6000
B-425 – Polypropylene Flag										
BMP51, 53	Fig. 48	MFT-01-425	B-425	Polypropylene Flag	BK on WT	0.788 (20.01)	1.18 (29.97)	-	200	R4300
B-499 – Nylon Cloth										
BMP41, 51, 53	Fig. 63	M-141-499	B-499	Nylon Cloth	BK on WT	1.000 (25.40)	1.000 (25.40)	0.250 (6.35)	90	R4300
BMP51, 53	Fig. 63	M-152-499	B-499	Nylon Cloth	BK on WT	1.500 (38.10)	0.500 (12.70)	0.250 (6.35)	160	R4300