




Passive Components > Resistors > Chassis Mount Resistors > Power Resistors: Aluminum Housed, HSA



Resistor Type: **Power Resistor**
Resistance Class: **Up to 1kΩ**
Resistance Value: **100 Ω**
Power Rating: **100 W**
Element Type: **Wire Wound**

[All Power Resistors: Aluminum Housed, HSA \(384\)](#)

Features

Product Type Features

Resistor Type	Power Resistor
Element Type	Wire Wound

Configuration Features

Number of Resistors	1
---------------------	---

Electrical Characteristics

Operating Voltage	1900 VDC
Resistance Class	Up to 1kΩ
Resistance Value	100 Ω
Power Rating	100 W
Passive Component Tolerance	5 %

Termination Features

Number of Terminations	2
------------------------	---



Chassis Mount Resistor Termination Type

Solder Lug

Mechanical Attachment

Panel Mount Feature Type	Flange with Mounting Holes
--------------------------	----------------------------

Dimensions

Product Height	26 mm[1.024 in]
Product Length	87.5 mm[3.445 in]
Product Width	47.5 mm[1.87 in]

Usage Conditions

Temperature Coefficient	±50 ppm/°C
-------------------------	------------

Packaging Features

Packaging Method	Loose Piece - Tray
------------------	--------------------

Product Compliance

For compliance documentation, visit the product page on [TE.com](#)>


EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	有害物质含量符合标准要求 No Restricted Substance(s) Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Hand solderable with lead free solder

Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>




Compatible Parts



TE Part # CAT-C339-H85913
Power Resistors: Aluminum Housed, HSA



TE Part # 1630027-1
HSC300 100R 5%



TE Part # 1625999-3
HSC100 10R 5%


Also in the Series | CGS HS




Automotive Housings(1)




Automotive Signal & Power Connector Housings(1)




Card Edge Connector Housings(1)



FFC Connectors(1)



High Speed Backplane Connectors(10)




RJ45 Connectors(1)

Customers Also Bought



TE Part #80650-000
LS809-52 LIQUID LEVEL SENSOR



TE Part #53264-2
TERMINAL,TERMI-FOIL 14-12



TE Part #5-534267-1
14 MODIV VRT DR DE 100/125



TE Part #4-794637-6
16P MICRO MNL ASSY,VRT,SMT LF






TE Part #965612-2
32POS MQS REC



TE Part #1625999-6
HSC100 15R 5%



TE Part #6-1879071-0
THS50 22K 5%



TE Part #6-2176360-7
RQ 0402 2K1 0.1% 10PPM 1K RL

TE Part #1SNS420000Z2802
XOD0000163876-A (X804-B - 1 OF 1)

TE Part #1-1617036-6
HFW4A1201S01 = 2100 HFW 4A REL

Documents

Product Drawings

HSC100 100R 5%

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1625999-1_AH.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1625999-1_AH.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1625999-1_AH.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

4-1773460-6_RESISTIVE_SOLUTIONS_RAIL

English

1309350_PASSIVE_COMPONENT

English

Aluminium Housed Power Resistors - Type HS Series

English

8-1773459-4_POWER_FILTERING_AND_RESISTIVE_SOLUTIONS_FOR_ELEVATORS_AND_ESCALATORS

English

HSC100100RJ

100 ohm, Wire Wound, 5 %, Power Resistor, 100 W, 2 Terminations, ± 50 ppm/ $^{\circ}$ C,
Solder Lug, Loose Piece - Tray, 26 mm [1.024 in] Height, CGS HS

