



Breather Drain – SIRA 99 ATEX 3050 U
 I M2 II, 2GD, EExe I & II (Stainless steel & brass only)
 II 2GD, EExe II (Nylon only)
 Enclosure type 4X IP66

SELECTION TABLE

Entry Thread	Material	Catalog #
M20	Brass	DPE1004S3
M20	Stainless Steel	DPE3004S3
M20	Nylon	DPE4004S3
M25	Brass	DPE1005S3
M25	Stainless Steel	DPE3005S3
M25	Nylon	DPE4005S3
1/2"	Brass	DPE1029S3
1/2"	Stainless Steel	DPE3029S3
3/4"	Brass	DPE1030S3
3/4"	Stainless Steel	DPE3030S3

Drainage Plug – Standard material is polyamide; PTB01 ATEX 1128X Ex 1126 Exe II

SELECTION TABLE

Thread 1	Diameter	Length 1	Length 2	Catalog #
M25 x 1.5	30.00	19.00	4.50	GHG 960 1927 R0105

Breathing and Drainage Plug – Standard material is glass-filled polyamide;
 SIRA 99 ATEX 3050 U Ex 1126 Exe II

SELECTION TABLE

Thread 1	Catalog #
M25 x 1.5	GHG 960 1954 R0002

All dimensions in millimeters unless otherwise noted.

Please refer to section 6F for additional breather and drain options.