



+ RELAYS, CONTACTORS & SWITCHES

TO-5/.100 GRID



✓ Active

TE CONNECTIVITY (TE)

JMSC-48XL=M39016/11-038L

CII

8-1617568-0

TE Internal Number: 8-1617568-0

Mil-Spec: M39016/11-038L

Alias ID: JMSC-48XL

Not EU RoHS Compliant

Not Yet Reviewed for EU ELV

Contact Arrangement 2 Form C, DPDT, 2 C/O

Input Voltage (VDC) 25.8

Coil Suppression Diode Without

MOSFET Driver Without

Transistor Driver Without

DOCUMENTATION —

No documentation available.

FEATURES +

Please review product documents or [contact us](#) for the latest agency approval information.

Product Type Features

MOSFET Driver Without

Product Type Relay

Coil Latching Without

Relay Type Military/Aerospace High Performance

Enclosure Type Hermetically Sealed

Configuration Features

Transistor Driver Without

Electrical Characteristics

Input Voltage (VDC) 25.8

Coil Suppression Diode Without

Coil Voltage (VDC) 48

Coil Resistance (Ω) 11000

Coil Power Rating (DC) (mW) 209

Coil Polarity Protection Diode Without

Contact Switching Voltage (Max) 28

Shock 75G's, 6ms

Vibration 30G's, 10 – 3000Hz

Actuating System DC

Coil Power Measurement Milliwatts

Coil Magnetic System Non-Polarized, Monostable

Contact Features

Contact Arrangement 2 Form C, DPDT, 2 C/O

Contact Current Rating (A) 1

Contact Current Class Low Level – 1 A

Termination Features

Termination Type PC Pins

Mechanical Attachment

Mounting Type Printed Circuit Board

Usage Conditions

Operating Temperature Range ($^{\circ}\text{C}$) -65 – 125

Statement of Compliance

Statement of Compliance

PDF