



20310-80

Products

- SOLENOID VALVES
- HOSE SETS
- SOLENOIDS
- ▶ RELAYS
- CUSTOM ASSEMBLIES

GUIDED SEARCH

Click a term to initiate a search.

Relay Type

- [General Purpose](#) (476)
- [Power](#) (303)
- [Magnetic Latching](#) (102)

Max Contact Rating

- [10 amps](#) (210)
- [5 amps](#) (203)
- [30 amps](#) (143)
- [35 amps](#) (140)
- [13 amps](#) (128)
- [15 amps](#) (54)
- [20 amps](#) (2)
- [11 amps](#) (1)

Contact Configuration

- [DPDT](#) (225)
- [SPDT](#) (191)
- [3PDT](#) (178)
- [DPST-NO](#) (44)
- [SPST-NO-DM](#) (39)
- [4PDT](#) (30)
- [DPST-NC](#) (30)
- [SPST-NC](#) (30)
- [SPST-NO](#) (30)
- [6PDT](#) (24)
- [more...](#)

Terminal Style

- [.187" QC terminals](#) (242)
- [.250" QC terminals](#) (237)
- [Pierced solder lugs .125"](#) (90)
- [Screw type](#) (82)
- [Octal plug \(8, 11 pins\)](#) (78)
- [Printed circuit pins](#) (72)
- [Pierced solder lugs](#) (54)
- [Octal plug \(8, 11, 20 pins\)](#) (30)
- [8-Pin Jones Plug](#) (2)

13 AMP COVERED PLUG-IN

[Specifications](#)
[Datasheet](#)
[REQUEST A QUOTE](#)

Relay Type:

General Purpose

Model:

166

Terminal Style:

.187" QC terminals

Contact

Configuration:

DPDT

Max Contact

Rating:

13 amps

Detailed Contact

Rating:

13 AMP OR 1/3 HP @120VAC
 13 AMP OR 1/2 HP @277VAC
 10 AMP AT 28VDC
 1 HP AT 277VAC-3PHASE
 3 AMP OR 3/4 HP @600VAC
 12 FLA, 35 LRA @ 15VAC

Contact Material:

MOVEABLE-SILVER CADMIUM OXIDE
 STATIONARY-FINE SILVER

Coil Voltage:

6 VDC

Cover Type:

Plain cover

Stocked:

Yes

Cover Type

[Open cover](#) (343)

[Plain cover](#) (313)

[Flange cover](#) (159)

[Top Mount Cover](#) (66)

[HOME](#) [PRODUCTS](#) [INDUSTRIES](#) [RESOURCES & CAD DOWNLOADS](#) [DISTRIBUTORS](#) [REQUEST A QUOTE](#) [ABOUT US](#) [CONTACT US](#)

2740 South 20th Street | Milwaukee, WI 53215 | 414.671.6800 | Fax: 414.671.6809 | sales@deltrol.com

[Sitemap](#) | ©2013 Deltrol Controls - A Division of Deltrol Corp.

Web Design by [Top Floor Technologies](#)