



## Circuit Board Indicators

## Panel Mount Indicators

## Solid State Lighting

## Traffic Signals

## Vehicle Lighting

## Rail

## Obstruction Lighting

## Hazardous Area Lighting

## Heliport Lighting

## how to purchase

[sales contacts](#)
[stock check](#)
[search](#)

## Product Line Search

Please select a Product Line to search.

Circuit Board Indicators

find

## Part # / Text Search

Part No.:

Text Search:

search

## quick links

## Dialight Corporate Video

Presentation at LightFair 2007 - "Presentation of White LEDs" : by Ian Ferguson, Georgia Tech in conjunction with Dialight Corp. [View PDF File](#)

Application Notes  
FAQs

Dialight Ltd (UK)  
Dialight Garufo  
Dialight BLP  
LumiDrives

## Circuit Board Indicators - Through Hole Indicators

P/N# 5532231110F

3 mm Lens

Description  
Package Options  
Product Type  
Sub Product Type  
Configuration  
Viewing  
Viewing Angle  
Test Current (mA)

3 mm Bi-Level CBI  
50 Pieces Per Bag  
Through Hole Indicators  
with Bi-Level Housing  
3 mm Lens  
Right Angle  
45  
10mA

## Absolute Maximum Ratings (Ta = 25 °)

Solder Temp  
Operating Temp  
Storage Temp

260Å° for 5 sec  
-55 to +100° C  
-55 to +100° C


RoHS /pB Free  
view PDF

## Operating Characteristics

| LED Position               | Found in position(s): 1 | Found in position(s): 2 |
|----------------------------|-------------------------|-------------------------|
| Color                      | Yellow                  | Red                     |
| Lamp Type                  | Single Color            | Single Color            |
| LED Type                   | High Efficiency         | High Efficiency         |
| Intensity Min (mcd)        | 10.0                    | 8.7                     |
| Intensity Typ (mcd)        |                         | 29.0                    |
| Intensity Max (mcd)        | 50                      |                         |
| Fwd Voltage Min            |                         |                         |
| Fwd Voltage Typ            |                         |                         |
| Fwd Voltage Max            |                         |                         |
| Dom Wavelength Min (nm)    |                         |                         |
| Dom Wavelength Typ (nm)    |                         |                         |
| Dom Wavelength Max (nm)    |                         |                         |
| Power Dissipation Max (mW) | 60                      | 100                     |
| Backlighting               |                         |                         |
| Pitch Between Vertical     |                         |                         |
| Pitch Between Horizontal   |                         |                         |
| Lum Intensity Min          |                         |                         |
| Lum Intensity Typ          |                         |                         |
| Lum Intensity Max          |                         |                         |

## Distributor Stock Check

Check stock with our distributors now.

5532231110F

[check stock](#)