

Dialight - Leader in LED Technology



- ? [Circuit Board Indicators](#)
- ? [Panel Mount Indicators](#)
- ? [Solid State Lighting](#)
- ? [Traffic Signals](#)
- ? [Vehicle Lighting](#)
- ? [Rail](#)
- ? [Obstruction Lighting](#)
- ? [Hazardous Area Lighting](#)
- ? [Heliport Lighting](#)

Circuit Board Indicators - Surface Mount Indicators	
P/N#	PLCC-2 Single Color
5973215307F	
Description	

Region:

Product Line:

Forward Current Continuous	30 mA
Forward Current Pulse	100 mA
Derating	from 40Â° @ .42mA/Â°C
Solder Temp	240Â° for 20 sec
Operating Temp	-55~+100° C
Storage Temp	-55~+100° C
Peak Wave Length	609

Distributor Stock Check

Check stock with our distributors now.



Check stock with our distributors now.




Please note that the stock check **is only applicable** to products *within* **Circuit Board Indicators** and **Panel Mount Indicators**.

Operating Characteristics	
LED Position	
Color	Orange
Lamp Type	Single Color
LED Type	AllnGaP
Intensity Min (mcd)	71.9
Intensity Typ (mcd)	90.0
Intensity Max (mcd)	
Fwd Voltage Min	1.9
Fwd Voltage Typ	2.4
Fwd Voltage Max	
Dom Wavelength Min (nm)	605
Dom Wavelength Typ (nm)	63
Dom Wavelength Max (nm)	
Power Dissipation Max (mW)	
Backlighting	
Pitch Between Vertical	
Pitch Between Horizontal	
Lum Intensity Min	
Lum Intensity Typ	
Lum Intensity Max	

Please select a Product Line to search.

Part No.:

Text Search:



Copyright 2006 Dialight. All rights reserved | [Privacy Policy](#)

[Dialight Corporate Video](#)

Presentation at LightFair 2007 - "Presentation of White LEDs" : by Ian Ferguson, Georgia Tech in conjunction with Dialight Corp. [View PDF File](#)

[Application Notes](#)
[FAQs](#)

[Dialight Ltd \(UK\)](#)
[Dialight Garufo](#)
[Dialight BLP](#)
[LumiDrives](#)