

- ? [Circuit Board Indicators](#)
- ? [Panel Mount Indicators](#)
- ? [Solid State Lighting](#)
- ? [Traffic Signals](#)
- ? [Vehicle Lighting](#)
- ? [Rail](#)
- ? [Obstruction Lighting](#)
- ? [Hazardous Area Lighting](#)
- ? [Heliport Lighting](#)

Circuit Board Indicators - Surface Mount Indicators	
P/N#	2 mm Lens Single Color
5973322307F	
Description	

Region:

Product Line:

Circuit Board Indicators

Reverse Current	100 @ Vr =5V
Forward Current Continuous	30 mA
Forward Current Pulse	100 mA
Derating	from 30° @ .36mA/°c
Reverse Voltage	5 V
Solder Temp	260° for 5 sec
Operating Temp	-55~+100° C
Storage Temp	-55~+100° C
Peak Wave Length	523

Distributor Stock Check

Check stock with our distributors now.

5973322307F

Check stock with our distributors now.

5973322307F

RoHS Compliant Product

Please note that the stock check **is only applicable** to products *within* **Circuit Board Indicators** and **Panel Mount Indicators**.

Please select a Product Line to search.

Circuit Board Indicators

Part No.:

Text Search:

Operating Characteristics	
LED Position	
Color	Green
Lamp Type	Single Color
LED Type	InGaN
Intensity Min (mcd)	160
Intensity Typ (mcd)	690.0
Intensity Max (mcd)	
Fwd Voltage Min	3.7
Fwd Voltage Typ	4.1
Fwd Voltage Max	
Dom Wavelength Min (nm)	525
Dom Wavelength Typ (nm)	114
Dom Wavelength Max (nm)	
Power Dissipation Max (mW)	
Backlighting	
Pitch Between Vertical	
Pitch Between Horizontal	
Lum Intensity Min	
Lum Intensity Typ	
Lum Intensity Max	

[Dialight Corporate Video](#)

Presentation at LightFair 2007 - "Presentation of White LEDs" : by Ian Ferguson, Georgia Tech in conjunction with Dialight Corp. [View PDF File](#)

[Application Notes](#)
[FAQs](#)

[Dialight Ltd \(UK\)](#)
[Dialight Garufo](#)
[Dialight BLP](#)
[LumiDrives](#)