

Datasheet

Item No. 78.181.0453.0

Modular insert FLE BUD 2S 1,5 03 AU

Modular connector system 2 pole + screen female contact profibus DP, 30V/1A/1,5Mbit/s, screw connection



Item No.	78.181.0453.0
EAN	4015573739734
order unit	5 Piece(s)

Technical data

General

Model	Female insert
Inflammability class of insulation material acc. with UL94	V0
Colour	Grey
Mating cycles	50
Pollution degree	3
Modular version	Yes
Operating temperature range min.	-20 °C
Operating temperature range max.	85 °C

Connection Data

Connection type	Screw connection
Number of poles	4
Plus switching contacts	0
Number of pole for rated current 2	0
Number of pole for rated current 3	0
Total number of poles (without ground contact)	4
With wire protection	Yes
Conductor cross section rigid (solid, stranded)	1.5
Protective contact	No

Technical Data UL/CSA

Min. conductor cross section flexible wire	0.5
Max. conductor cross section flexible wire	1.5
Conductor cross section flexible AWG wire	28-16 AWG

Model

With housing	No
--------------	----

Contacts

Contact material	Copper alloy
Surface	Gilt

Wire strip length	5 mm
Screws head design/recomm. Torque	
Mounting screws	M3/0.5-0.7 Nm Slot
Clamping screws	H1/0.2 Nm
Technical Data DIN EN 61984	
Nominal voltage	30
Rated voltage face/ground	30
Nominal current	1
Rated impulse voltage	0.8 kV