

Datasheet

Item No. 92.033.0058.1

Female connector GST18I3L B1H SW

Device connectors, PCB mount, GST18i3, 3 pole, horizontal, female, 250V/16A, color of coding: black



Item No.	92.033.0058.1
EAN	4015573432024
order unit	100 Piece(s)

Approvals



Technical data

General

Rated current	16 A
Rated voltage	250 V
Pollution degree	2
Mechanical coding	Yes
Rated impulse voltage	4 kV
Interlockable	Yes
Color of coding/ contact carrier	Black
Terminations per pole	1

Model

Model	Bus
Number of poles	3
Connection type	Soldering connection
Connecting thread metric	No thread
Angle of plug	Square
Degree of protection (IP)	IP40
Built-in component	Soldering connection

Material

Housing material	Polyamide
Halogen free	Yes
Contact material	CuZn
Insulation components continuous temperature	100 °C
Surface finish	Tin-plated

Dimensions

Length	24 mm
Width	28.2 mm
Height	13 mm

Drawings

Schnitt A-A
cross section

Schnitt B-B
cross section

Weitere Daten siehe Katalog
further data see catalog

Teilenummer part number	Farbe colour	Typ type	Freifolien nach DIN 19891 Leiterabgriffe 130				2D - Zeichnung, keine manuellen Änderungen			1. Verwendung: -		Bl. 1	von 1
92.033.0058.0	weiss white	GST1813L B1H ws	2:1	Material und Oberfläche:	2005	Tig	Name	Zeichnung Nr.:		92.033.0058.0 01K		Index	
92.033.0058.1	schwarz black	GST1813L B1H sw		Verf.:	mm	Ø	mm	Stempel:	Einsatz für:				
					Typ		BUCHSENTEIL Lötansch./rechth./Soldered connection horizontal Female connector						
							Änderung						

A
1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
M1
M2
M3
L
G
i
1.1
2.1
1.1