



Quality Products. Service Excellence.

Horizontal Ring Cable Manager *RB-HRM Series*

Features



- Constructed in 16-gauge steel.
- Flanged at front for added strength.
- Designed to fit standard 19" rails.
- Rings extend 3.69 inches from panel front.
- Includes four (4) cable pass-through cutouts.
- Designed to mount two (2) units back-to-back.
- Finished in textured black powder paint.
- Requires mounting hardware.
- RoHS and REACH compliant.
- Manufactured in North America.



Help us improve the RB-HRM Series

We're considering adding additional sizes. Would you prefer a deeper depth manager? *

- Current depth is fine
- Four (4) inch
- Five (5) inch
- Seven (7) inch
- Greater than seven (7) inch



Part of the Rack Basics® line of economy rack solutions.

Accessories

- Mounting Hardware
- Hook and Loop Roll

Part No.	Overall Dimensions			Usable Mounting Dimensions	
	Height	Width	Depth	Rack Units	Height
RB-HRM1	1.72	19.00	3.69	1U	1.75
RB-HRM2	3.22	19.00	3.69	2U	3.50

Estimated Cable Fill Capacities

Rack Units	Description	Opening Quantity	Recommended Cable Fill (50% Fill Ratio)			Maximum Cable Fill (100% Fill Ratio)		
			Cat 5e	Cat 6	Cat 6a	Cat 5e	Cat 6	Cat 6a
1U	Channel Opening	1	50	32	22	100	64	45
	Rear Pass Through	4	16	10	7	32	20	14
2U	Channel Opening	1	102	65	45	204	130	91

Rack Units	Description	Opening Quantity	Recommended Cable Fill (50% Fill Ratio)			Maximum Cable Fill (100% Fill Ratio)		
			Cat 5e	Cat 6	Cat 6a	Cat 5e	Cat 6	Cat 6a
	Rear Pass Through	4	25	16	11	49	32	22

Data subject to change without notice

© 2019. Hammond Manufacturing Ltd. All rights reserved.