

Marine Products Internationally Rated

16, 32, 63 Ampere, 240 Volt
Pin and Sleeve Devices



HBL316B6W



HBL316R6W



HBL316C6W



HBL316P6W



PC320



BB201W

IP67 SUITABILITY

UL Classified to IEC 60309-1 and 60309-2

Devices are 2 pole plus earth (⊕) rated 240V in either 16A, 32A or 63A.

2 Pole ⊕ ⊕ 16A 240V



Description	Catalog Numbers
Shore power inlet with mounting holes 3 1/8" (79.3) on centers and 2 23/32" (69.1) diameter on rear portion.	HBL316B6W
Connector body with cord grip range of .360"-.830" (9.1-21.1).	HBL316C6W
Shore power receptacle with mounting holes 3 1/8" (79.3) on centers and 2 23/32" (69.1) diameter on rear portion.	HBL316R6W
Plug with cord grip range of .360"-.830" (9.1-21.1).	HBL316P6W
Closure plug for #HBL316B6W. Not CSA.	PC320
Back box for inlets and receptacles is cast aluminum with corrosion resistant alkyd-based enamel finish and two 3/4" N.P.T. hubs.	BB201W
Feed-thru box for inlets and receptacles is cast aluminum with corrosion resistant alkyd-based enamel finish and one 3/4" N.P.T. hubs.	FT202W

2 Pole ⊕ ⊕ 32A 240V

Description	Catalog Numbers
Shore power inlet with mounting holes 3 1/8" (79.3) on centers and 2 23/32" (69.1) diameter on rear portion.	HBL332B6W
Connector body with cord grip range of .450"- 1.250" (11.4-31.8).	HBL332C6W
Shore power receptacle with mounting holes 3 1/8" (79.3) on centers and 2 23/32" (69.1) diameter on rear portion.	HBL332R6W
Plug body with cord grip range of .450"- 1.250" (11.4-31.8).	HBL332P6W
Closure plug for #HBL332B6W. Not CSA.	PC3430
Back box for inlets and receptacles is cast aluminum with corrosion resistant alkyd-based enamel finish and one 1" N.P.T. hub.	BB301W

2 Pole ⊕ ⊕ 63A 240V

Description	Catalog Numbers
Shore power inlet with mounting holes 3 7/8" (98.4) on centers and 3 15/32" (88.1) diameter on rear portion.	HBL363B6W
Connector body with cord grip range of .700"- 1.450" (17.8-36.8).	HBL363C6W
Shore power receptacle with mounting holes 3 7/8" (98.4) on centers and 3 15/32" (88.1) diameter on rear portion.	HBL363R6W
Plug body with cord grip range of .700"- 1.450" (17.8-36.8).	HBL363P6W
Closure plug for #HBL363B6W. Not CSA.	PC60
Back box with 1 1/2" N.P.T. hub.	BB601W
Back box for inlets and receptacles has 15° angle section which can be installed in any of 4 positions. Box is cast aluminum with corrosion resistant gray alkyd-based enamel finish and 1 1/2" N.P.T. hub which can be mounted for either top or bottom feed.	FW60100

Marine Products

Internationally Rated

16, 32 Ampere, 230 Volt

Ship-to-Shore Power System

Hubbell offers the only CE certified electrical shore power system truly dedicated for boats destined for Europe and the International community. Hubbell's offering of international shore power inlets is available in stylized #316 Type Stainless Steel as well as attractive white non-metallic types resembling our domestic offering in style and appearance but are not interchangeable with the domestic shore power system.

Utilizing standard NEMA (National Electrical Manufacturer's Association) configurations not typically used in the marine market, Hubbell can offer a safe and non-interchangeable 16 Amp 230 Volt system and 32 Amp 230 Volt system for use with 50 cycle systems. The system includes white power supply cables (one-end, female only) in both the 16 Amp and 32 Amp categories.

IP56


SUITABILITY

**16 Amp 230 Volt
Ship-To-Shore Power System**

Description	Catalog Numbers
Non-metallic, white, stylized, U.V. resistant shore power inlet. White Centrex cover makes the inlet weatherproof when closed. Mounting holes are 2 3/8" (60.3) on centers and match most existing mounting patterns. Rear enclosure strain/relief cap is provided.	HBL316NM
Traditional, stainless steel shore power inlet has new easy-to-wire terminations. Interior is transparent for quick and easy visual inspection. Interior is shielded from the elements by a gasketed, self-closing cover, watertight when cover is screwed in place. Mounting holes are 2 3/8" (60.3) on centers. Mounting screws and gasket included. Protective rear enclosure/strain relief also included.	HBL316SSX
25' (7.6m) white, vinyl jacketed power supply cord with female (boat side) end only; other end blunt cut.	HBL316CSW25
50' (15.2m) white, vinyl jacketed power supply cord with female (boat side) end only; other end blunt cut.	HBL316CSW
Yellow locking connector replacement end for #HBL316CSW25 & #HBL316CSW.	HBL316CRC
White Seal-Tite cover with threaded sealing ring for use with #HBL316CRC and #HBL332CRC connector bodies.	HBL103RX

32 Amp 230 Volt, 50 Cycle Ship-To-Shore Power System

Description	Catalog Numbers
Non-metallic, white, stylized, U.V. resistant shore power inlet. White Centrex cover makes the inlet weatherproof when closed. Mounting holes are 2 3/8" (60.3) on centers and match most existing mounting patterns. Rear enclosure/strain relief cap is provided.	HBL332NM
Traditional, stainless steel shore power inlet has new easy-to-wire terminations. Interior is transparent for quick and easy visual inspection. Interior is shielded from the elements by a gasketed, self-closing cover, watertight when cover is screwed in place. Mounting holes are 2 3/8" (60.3) on centers. Mounting screws and gasket included. Protective rear enclosure/strain relief also included.	HBL332SSX
50 ft. (15.2m) white, vinyl jacketed power supply cord with female (boat side) end only; other end blunt cut.	HBL332CSW
Yellow locking connector replacement end for #HBL332CSW.	HBL332CRC
White Seal-Tite cover with threaded sealing ring for use with #HBL316CRC and #HBL332CRC connector bodies.	HBL103RX

HBL316NM
HBL332NMHBL316SSX
HBL332SSXHBL316CSW25
HBL316CSW
HBL332CSWHBL316CRC
HBL332CRC

HBL103RX