

# HBL2313VBK -- Twist-Lock Valise Connector Body



2P3W, 20A 125V, L5-20R, Black Nylon

## Product Specifications

### Product Type



Twist-Lock  
Devices

<b>Product Item</b>	Connector Body
<b>Wiring Scheme</b>	2-Pole, 3-Wire Grounding
<b>Amperage</b>	20A
<b>Voltage</b>	125V AC
<b>NEMA Configuration</b>	L5-20R
<b>Item Style</b>	Valise
<b>Device Color</b>	Black
<b>Cord Dia.</b>	.325"-.930" (8-24)
<b>Housing Material</b>	Black nylon
<b>Cord Clamp Material</b>	Natural (white) nylon
<b>Terminal Clamp Material</b>	Cold rolled steel-nickel-plated
<b>Terminal Screw Material</b>	#8-32 Steel (copper flash, nickel plate & molykote)
<b>Ground Screw Material</b>	#8-32 Steel (green finish)
<b>Cord Clamp Screw Material</b>	Steel zinc plate
<b>Contact Spring Material</b>	Brass
<b>Ground Contact Material</b>	Brass
<b>Ratings</b>	Molded In or Stamped On
<b>Catalog No</b>	Permanently ink marked on product
<b>Dielectric Voltage Withstand</b>	2,000V minimum
<b>Current Interrupting</b>	Certified for current interrupting at full rated current
<b>Temperature Rise</b>	Max 30C temperature rise at full rated current after 50 cycles of overload at 150% of rated current at a power factor of .75.
<b>Cord Accommodation</b>	Round portable service cords of diameters commensurate with the device rating as defined in UL Standard 62, CSA C22.2 No. 49.
<b>Terminal Accommodation</b>	20A #12 AWG
<b>Terminal Identification</b>	Terminals identified in accordance with UL 498 (X, Y, Z, White, Green)
<b>Flammability</b>	HB or better per UL 94 or CSA 22.2 No. 0.6
<b>Operating Temperatures</b>	Maximum Continuous 75 C Minimum -40 C (w/o impact)
<b>Moisture Resistance</b>	IP20
<b>Listings</b>	UL/CSA
<b>UPC Number</b>	783585043029
<b>Weight in LBs</b>	0.25
<b>Link to Drawing Library</b>	<a href="#">Click here for Library</a>
<b>Link to PDF Catalog</b>	<a href="#">Click here for Catalog</a>

