

# | P265

## STAINLESS STEEL PRESSURE TRANSDUCER

### Introduction

The model P265 is based on Kavlico’s field proven ceramic capacitive technology with the latest state-of-the-art ASIC. Featuring a 303SS housing, the P265 is designed for general use wherever a rugged and reliable pressure transducer is required. The P265 package has a built-in MetriPack 150, electrical connector and supports popular process connection threads. The P265 is offered with a variety of seal materials and is suitable for many diverse applications. Specifically intended for OEM applications, the P265 delivers a cost effective solution without compromising performance or reliability.



### Features

- Dry Media <sup>(1)</sup>
- Superior Long Term Stability
- Excellent Repeatability/Hysteresis
- Superior EMI/RFI Rejection
- Low Power Consumption
- Linear Output
- Temperature Compensated
- Over-Voltage, Reverse Polarity & Short Circuit Protection
- Ten Million Cycle Life Expectancy
- Outstanding Shock & Vibration Performance

### Applications

- Steam Sterilizers
- Gasoline & Diesel Engines
- Natural Gas & CNG Engines
- Agricultural Chemical Equipment
- Level Measurement
- Test Equipment
- Injection Molding
- Coolant Pressure
- Industrial Compressors

### MAIN FEATURES

|                              |                                                            |
|------------------------------|------------------------------------------------------------|
| <b>Pressure Ranges</b>       | 0 to 15 up to 0 to 1000 PSI                                |
| <b>Electrical Connection</b> | Packard Electric Metri-Pack 150 Series, 12" 20" AWG leads  |
| <b>Pressure Connection</b>   | 1/4-18 NPT (external), 3/8-24 UNF-2A (male) <sup>(2)</sup> |
| <b>Housing Material</b>      | 303 Stainless Steel                                        |
| <b>Output Signal</b>         | 0.5 - 4.5 VDC                                              |



## Pressure Ranges

| From 0 to ...  | PSIA,<br>PSIG,<br>PSIS<br>(gage) | 15   | 20   | 30   | 50   | 75   | 100  | 150  | 200  | 300  | 500  | 750  | 1000 |
|----------------|----------------------------------|------|------|------|------|------|------|------|------|------|------|------|------|
| Proof pressure | PSIA,<br>PSIG,<br>PSIS           | 75   | 100  | 150  | 250  | 375  | 300  | 450  | 600  | 900  | 1500 | 1500 | 2000 |
| Burst pressure | PSIA,<br>PSIG,<br>PSIS           | 1000 | 1000 | 1000 | 1000 | 1000 | 2000 | 2000 | 2000 | 2000 | 2000 | 2000 | 2000 |

## Physical

|                       |                                                                                                       |
|-----------------------|-------------------------------------------------------------------------------------------------------|
| Operating Life Cycle  | min. 10 million full pressure cycles over the full range                                              |
| Vibration Resistance  | 10 G's peak to peak sinusoidal (10 to 2000 Hz)                                                        |
| Shock Resistance      | 75 G's ½ sinewave                                                                                     |
| Drop Test             | 1 meter drop on concrete as per SAE J1455 / DIN EN 60068-2-3-1                                        |
| Weight                | ≤ 100 grams (without mating connector)                                                                |
| Ingress Protection    | IP 65 or IP67 - depending on electrical connector                                                     |
| Operating Temperature | -40°C to 125°C (depending on seal material) <sup>(2)</sup>                                            |
| Storage Temperature   | -40°C to 125°C (depending on seal material) <sup>(2)</sup>                                            |
| Media                 | All class II fluids and gases compatible with stainless steel 303 and the internal seal ring material |

## Performance

|                                 |                                                                         |
|---------------------------------|-------------------------------------------------------------------------|
| Total error band <sup>(3)</sup> | +/-2% of span (-20 ≤ T ≤ 100° C) +/-3% of span (T < -20° C, T < 100° C) |
| Stability coefficient           | +/-0.5 % of full span over 1 year                                       |
| Temp. Coefficients - Zero       | 0.2 % of span / 10 K within temperature range 0°C to + 80°C.2 %         |
| Temp. Coefficients - Span       | 0.2 % of span / 10 K within temperature range 0°C to + 80°C.2 %         |




## Electrical

|                             |                                                                    |
|-----------------------------|--------------------------------------------------------------------|
| Output Signal               | 0.5...4.5 VDC Ratiometric                                          |
| Operating Supply Signal     | 5 VDC ± 10%                                                        |
| Power Consumption           | ≤ 25 mW                                                            |
| Overvoltage Protection      | 16 VDC                                                             |
| Short-circuit Proofness     | Yes <sup>(4)</sup>                                                 |
| Insulation Voltage          | 500 VDC                                                            |
| Reverse Polarity Protection | Yes <sup>(5)</sup>                                                 |
| Load                        | ≥ 25 kΩ                                                            |
| Response Time               | 15 ms max. to 63% of full scale pressure with step change on input |



## DIMENSIONS

Dimensions in mm [Inch]



Before installation and operation, ensure that the appropriate pressure sensor has been selected in terms of pressure range, design and specific measuring conditions. Non-compliance can result in serious injury and/or damage to the equipment.

Warning: The product information contained in this catalogue is given purely as information and does not constitute a representation, warranty or any form of contractual commitment. Kavlico reserve the right to modify their products without notice. It is imperative that we should be consulted over any particular use or application of our products and it is the responsibility of the buyer to establish, particularly through all the appropriate tests, that the product is suitable for the use or application. Under no circumstances will our warranty apply, nor shall we be held responsible for any application (such as any modification, addition, deletion, use in conjunction with other electrical or electronic components, circuits or assemblies, or any other unsuitable material or substance) which has not been expressly agreed by us prior to the sale of our products.



## GENERAL NOTES

- <sup>(1)</sup> For wet conductive media please contact us
- <sup>(2)</sup> For more options see Ordering Options
- <sup>(3)</sup> Including non-linearity, hysteresis, non-repeatability, zero point and full scale error corresponds to error of measurement per IEC 61298-2). Adjusted in vertical mounting position with pressure port down
- <sup>(4)</sup> For min. 3 intervals at 5 minutes each
- <sup>(5)</sup> For min. 10 seconds on assigned pins



## ORDERING OPTIONS

Example : P265-500S-F1-A

P265 Pressure Transmitter, 0-500 PSIS (Sealed Gage), with Ethylene Propylene Seal Material, 1/4 - 18 NPT Pressure Connection and Mating Connector

|                                       |                    |            |          |          |          |          |
|---------------------------------------|--------------------|------------|----------|----------|----------|----------|
| <b>Family</b>                         | <b>P265</b>        | <b>500</b> | <b>S</b> | <b>F</b> | <b>1</b> | <b>A</b> |
| <b>P265</b>                           |                    |            |          |          |          |          |
| <b>Pressure Ranges</b>                |                    |            |          |          |          |          |
| 15: 0 - 15 PSI                        | 150: 0 - 150 PSI   |            |          |          |          |          |
| 20: 0 - 20 PSI                        | 200: 0 - 200 PSI   |            |          |          |          |          |
| 30: 0 - 30 PSI                        | 300: 0 - 300 PSI   |            |          |          |          |          |
| 50: 0 - 50 PSI                        | 500: 0 - 500 PSI   |            |          |          |          |          |
| 75: 0 - 75 PSI                        | 750: 0 - 750 PSI   |            |          |          |          |          |
| 100: 0 - 100 PSI                      | 1000: 0 - 1000 PSI |            |          |          |          |          |
| <b>Reference</b>                      |                    |            |          |          |          |          |
| A: Absolute                           |                    |            |          |          |          |          |
| G: Gage                               |                    |            |          |          |          |          |
| S: Sealed Gauge                       |                    |            |          |          |          |          |
| <b>Seal Material</b>                  |                    |            |          |          |          |          |
| B: Nitrile                            |                    |            |          |          |          |          |
| C: Neoprene                           |                    |            |          |          |          |          |
| D: Fluorocarbon                       |                    |            |          |          |          |          |
| E: Fluorosilicone                     |                    |            |          |          |          |          |
| F: Ethylene Propylene                 |                    |            |          |          |          |          |
| <b>Pressure Connection</b>            |                    |            |          |          |          |          |
| 1: 1/4 - 18 NPT (External Threads)    |                    |            |          |          |          |          |
| 2: 3/8 - 24 UNF-2A (Male)             |                    |            |          |          |          |          |
| 4: 1/8 - 27 NPT                       |                    |            |          |          |          |          |
| <b>Built-in Electrical Connection</b> |                    |            |          |          |          |          |
| A: Packard with Mating Connector      |                    |            |          |          |          |          |
| B: 12", 18 AWG Leads                  |                    |            |          |          |          |          |
| C: Packard without Mating Connector   |                    |            |          |          |          |          |



## AGENCY APPROVALS & CERTIFICATIONS



ROHS 2011/65/EU ROHS Directive

Sensata Technologies, Inc. ("Sensata") data sheets are solely intended to assist designers ("Buyers") who are developing systems that incorporate Sensata products (also referred to herein as "components"). Buyer understands and agrees that Buyer remains responsible for using its independent analysis, evaluation and judgment in designing Buyer's systems and products. Sensata data sheets have been created using standard laboratory conditions and engineering practices. Sensata has not conducted any testing other than that specifically described in the published documentation for a particular data sheet. Sensata may make corrections, enhancements, improvements and other changes to its data sheets or components without notice.

Buyers are authorized to use Sensata data sheets with the Sensata component(s) identified in each particular data sheet. HOWEVER, NO OTHER LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE TO ANY OTHER SENSATA INTELLECTUAL PROPERTY RIGHT, AND NO LICENSE TO ANY THIRD PARTY TECHNOLOGY OR INTELLECTUAL PROPERTY RIGHT, IS GRANTED HEREIN. SENSATA DATA SHEETS ARE PROVIDED "AS IS". SENSATA MAKES NO WARRANTIES OR REPRESENTATIONS WITH REGARD TO THE DATA SHEETS OR USE OF THE DATA SHEETS, EXPRESS, IMPLIED OR STATUTORY, INCLUDING ACCURACY OR COMPLETENESS. SENSATA DISCLAIMS ANY WARRANTY OF TITLE AND ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, QUIET ENJOYMENT, QUIET POSSESSION, AND NON-INFRINGEMENT OF ANY THIRD PARTY INTELLECTUAL PROPERTY RIGHTS WITH REGARD TO SENSATA DATA SHEETS OR USE THEREOF.

All products are sold subject to Sensata's terms and conditions of sale supplied at [www.sensata.com](http://www.sensata.com) SENSATA ASSUMES NO LIABILITY FOR APPLICATIONS ASSISTANCE OR THE DESIGN OF BUYERS' PRODUCTS. BUYER ACKNOWLEDGES AND AGREES THAT IT IS SOLELY RESPONSIBLE FOR COMPLIANCE WITH ALL LEGAL, REGULATORY AND SAFETY-RELATED REQUIREMENTS CONCERNING ITS PRODUCTS, AND ANY USE OF SENSATA COMPONENTS IN ITS APPLICATIONS, NOTWITHSTANDING ANY APPLICATIONS-RELATED INFORMATION OR SUPPORT THAT MAY BE PROVIDED BY SENSATA.

Mailing Address: Sensata Technologies, Inc., 529 Pleasant Street, Attleboro, MA 02703, USA.

## CONTACT US

### Americas

+1 (800) 350 2727

[sensors@sensata.com](mailto:sensors@sensata.com)

### Europe, Middle East & Africa

+33 (3) 88 20 8080

[position-info.eu@sensata.com](mailto:position-info.eu@sensata.com)

### Asia Pacific

[sales.isasia@list.sensata.com](mailto:sales.isasia@list.sensata.com)

China +86 (21) 2306 1500

Japan +81 (45) 277 7117

Korea +82 (31) 601 2004

India +91 (80) 67920890

Rest of Asia +886 (2) 27602006  
ext 2808