

POWER DISTRIBUTION BLOCK

134x553

Replace "x" with 1, 2, or 3 for number of poles



Wire Range

- Line: (1) 400 kcmil - #6 AWG (185mm² - 16mm²)
- Load: (6) #2 - #14 AWG (25mm² - 2.5mm²)

Electrical Ratings

- 335 Amps
- 600V per UL 1953 & CSA 22.2 No.158, class B & C requirements
- Short Circuit Current Rating (SCCR): See SCCR section for specifications
- CU7AL - 75°C connector terminal rating with copper or aluminum wire
- Factory & Field Wiring


Agency Compliance

- cULus - UL Listed, investigated to UL 1953, UL File QPQS.E309401 and UL evaluated to CSA 22.2 No 158 File no. QPQS7.309401


Material Information

- Insulator base:
 - Thermoplastic
 - Flammability rating of insulator base UL94V0
 - Insulator base temperature rating: -40°C to 125°C (UL RTI)
- Connector: aluminum, tin plated
- Line terminal set screws: aluminum, tin plated
- Load terminal set screws: steel, nickel plated
- Connector mounting screws: steel, zinc plated
- RoHS compliant

Termination Specifications

Line Side	Wire Size (CU Stranded)	Torque	Wires / Terminal	Wire Class (UL) ¹
	400 - 350 kcmil	31.1 N·m (275 lbf·in)	1	B, C
	300 - 2	31.1 N·m (275 lbf·in)	1	B, C, G, H, I (DLO)
	4 - 6	31.1 N·m (275 lbf·in)	1	B, C

- Aluminum wire range: 400 kcmil - #6 AWG
- Wire strip length: 1 1/8 in. (29mm)
- Terminal screw drive: 5/16 in. hex

Load Side	Wire Size (CU Stranded)	Torque	Wires / Terminal	Wire Class (UL) ¹
	2	5.6 N·m (50 lbf·in)	1	B, C
	4 - 6	5.1 N·m (45 lbf·in)	1	B, C, G, H, I (DLO)
	8	4.5 N·m (40 lbf·in)	1 - 2 ²	B, C, G, H, I (DLO)
	10	4 N·m (35 lbf·in)	1 - 2	B, C, I (DLO)
	12 - 14	4 N·m (35 lbf·in)	1 - 2	I (DLO)
1 - 4			B, C	

- Solid copper wire range: 10 - 14
- Aluminum wire range: 2 - 6 AWG
- Wire strip length:
 - 9/16 in. (14mm)
 - 1 1/16 in. (27mm)
- Terminal screw drive: 5/32 in. Hex

¹ For information on copper stranded wire classes please reference: <http://www.marathonsp.com/CatalogPDFs/Flexible-Stranded-Wire.pdf>

² Multiple wire rating applies to classes B, C, & I only

Short Circuit Current Ratings (SCCR)

- The suitable conductor ranges are limited to the table values only for achieving the SCCR in excess of the default rating of 10,000A.
- Other conductor combinations within the "Terminal Specifications" noted are suitable for achieving a SCCR of 10,000A (the default rating of terminal blocks).
- Enclosure size – For SCCR's greater than the default of 10KA, the minimum enclosure size is 16x12x6. When using the default rating, there are no enclosure limitations other than proper fit of the product.

SCCR With Fuses

Wire Cass	Suitable Conductors		Max Overcurrent Protection Fuse Required Amp Rating / Class						SCCR RMS Sym. Amps 600V. Max
	Line	Load	J	T	RK1	RK5	G	CC	
B, C	400 - 3/0	2 - 6	600	600	600	200	60	30	100,000
B, C	400 - 6	2 - 10	300	300	200	100	60	30	100,000
G, H, I (DLO)	250 - 1/0	4 - 10	400	400	400	100	60	30	100,000
G, H, I (DLO)	250 - 2	4 - 14	125	125	100	30	60	30	100,000
*	400 - 6	2 - 14	None (Default Rating)						10,000

* Any wire class evaluated (see terminal specification section)

Installation & Accessories

- Mounting (Panel):
 - For use with #10 fastener.
 - Mounting torque to be determined in end use application not to exceed 25-30 lbf-in (2.8 - 3.4 N·m).
- Covers:
 - Snap on hinge cover available upon request
 - Catalog number:
 - For 3-Pole (1343xxx), CH1343
 - For 2-Pole (1342xxx), CH1341 (2x For each pole)
 - For 1-Pole (1341xxx), CH1341
 - Cover is polycarbonate

Drawing

