

T-3mm Dual Tower with Standoff, 0.175" Leadframe Offset

INDEX

PRODUCT TREE



- [Product Table](#)
- [Applications / Uses](#)
- [Features / Options](#)
- [Order Samples](#)
- [Stock/Price Request](#)
- [Sales and Tech Support](#)

1. [Product Gallery](#)
2. [eLeds.com](#)
3. [PCB Indicator](#)
4. [Dome PCB Indicator](#)
5. [3mm Dome PCB Indicators](#)
6. [T-3mm Dual Tower with Standoff, 0.175" Leadframe Offset](#)

SPEC! Image next to part no. indicates cad file.

Lumex drawings are in PDF format. If you don't have Adobe Acrobat, click on this icon to

[download a free copy](#)



Lumex Part Number	BRIGHTNESS	Dice Material	Emitted Color	Peak (nm)	Epoxy Lens	Operating Current (mA)	Operating TYP,Vf (V)	Brightness TYP, mcd	Brightness @ mA	View Angle 2x THETA
SSF-LXH240GGD SPEC!	STANDARD	Gap	Green ■	565	Green Dfsd D	5-25	2.1	30	20	60
SSF-LXH240IID SPEC!	STANDARD	GaAsP	High Intensity Red ■	635	Red Dfsd D	5-25	2.1	30	20	60
SSF-LXH240SISID SPEC!	HIGH	AlInGaP	Super High Intensity Red ■	636	Red Dfsd D	5-25	2.0	100	20	60
SSF-LXH240SOSOD SPEC!	HIGH	AlInGaP	Sup Orange ■	610	Orange Dfsd D	5-25	2.0	100	20	60
SSF-LXH240SRSD SPEC!	STANDARD	GaAlAs	Sup Red ■	660	Red Dfsd D	5-25	1.8	80	20	60
SSF-LXH240SUGSUGD SPEC!	HIGH	AlInGaP	Sup Ultra Green ■	574	Green Dfsd D	5-25	2.2	60	20	60
SSF-LXH240SYSYD SPEC!	HIGH	AlInGaP	Sup Yellow ■	590	Yellow Dfsd D	5-25	2.0	100	20	60
SSF-LXH240USBSBD SPEC!	HIGH	InGaN/SiC	Ultra Sup Blue ■	470	Blue Dfsd D	5-25	3.5	80	20	60
SSF-LXH240YYD SPEC!	STANDARD	GaAsP	Yellow ■	585	Yellow Dfsd D	5-25	2.1	30	20	60

Applications / Uses

[\[top of page\]](#)

- Board Level Status Indicators
- Board Level Fault Indicators

- Circuit Troubleshooting Indicators
- Warning/Alarm Lights
- Backlighting of Overlays
- Post Lighting Switches and Keypads

Features / Options

[\[top of page\]](#)

- State-of-the-Art, Chip Technology
- Easy Drop-In-Board Installation
- Right Angle to the Board Position
- Choice of Colors and Lens Finishes
- Low Current Versions Available
- Color or Intensity Sorting Available
- Blinking LED
- With Internal Resistor for 5V and 12V Operation
- Black or Gray Holders for High Contrast
- Color Combinations

[Home](#)

[What's
New](#)

[Product
Gallery](#)

[Product
Search](#)

[X-Ref Search
Engine](#)

[Tech
Notes](#)

[Sales and Tech
Support](#)

[Corporate
Info](#)

290 East Helen Road Palatine, IL 60067 Telephone: (847) 359-2790 Facsimile: (847) 359-8904 E-mail us at sales@lumex.com

© 1997-2001 Lumex, Inc.