


DATE	REVISIONS	REV
8-16-94	CHG'D. STAND-OFF ON HOLDER BOTTOM./	A
11-29-94	UPDATED SPECS./	B
2-6-95	CHG'D. HOLDER BOTTOM./	C
10-5-95	REF ECN 10100./	D
2-6-96	REF ECN 10104./	E



BILL OF MATERIALS:

1. SSL-LX3044YD LED.
2. SSL-LX3044GD LED.
3. SSH-LXH240 HOLDER. MATERIAL: BLACK NYLON 94V-0.

RELIABILITY NOTE

OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.

DRAWING NUMBER
SSF-LXH240YGD

REV
E

ELECTRO-OPTICAL CHARACTERISTICS TA=25 °C I_f=20mA

PARAMETER	MIN	TYP	MAX	UNITS	TEST COND
PEAK WAVELENGTH		585 (YELLOW)		nm	
		565 (GREEN)		nm	
FORWARD VOLTAGE (Y/G)		2.1	2.8	V _f	
REVERSE VOLTAGE	5.0			V _r	I _r =100uA
AXIAL INTENSITY (Y/G)		15		mcd	I _f =20mA
VIEWING ANGLE		80		2x theta	
EMITTED COLOR:	POS. 1 - YELLOW		POS. 2 - GREEN		
EPOXY LENS FINISH:	POS. 1 - YELLOW DIFFUSED		POS. 2 - GREEN DIFFUSED		

LIMITS OF SAFE OPERATION AT 25 DEG. C

PARAMETER	MAX	UNITS
Ⓐ PEAK FORWARD CURRENT (Y/G)*	150/150	mA
Ⓑ STEADY CURRENT (Y/G)	30/25	mA
Ⓒ POWER DISSIPATION (Y/G)	105/105	mW
DERATE FROM 25 °C	-1.8	mW/ °C
OPERATING, STORAGE TEMP.	-40 TO +85	°C
LEAD SOLDERING TEMP.	+260	°C
2.0mm FROM BODY		3 SEC. MAX

* t<10μs

LUMEX
OPTO COMPONENTS INC.

292 E. HELLEN ROAD
PALATINE, ILLINOIS 60067
(708) 359-2790

CONFIDENTIAL INFORMATION
THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX OPTO/COMPONENTS, INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX OPTO/COMPONENTS, INC. THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

DATE: 2-2-93	DWN:	CHK'D:	APPD:
SCALE: N/A			

T-3mm LED, RIGHT ANGLE FAULT INDICATOR,
YELLOW/GREEN DIFFUSED

PAGE 1 OF 1	DRAWING NUMBER SSF-LXH240YGD	REV E
-------------	---------------------------------	----------