



Specifications:

Rating: 300V 8A(IEC250V 10A)
 Insulation Withstand Voltage: AC 2000V Min
 Insulation Resistance: 500 MΩ or more at DC500V
 Using Temperature Range: -40°C to +105°C
 Suitable Electric Wire: 24 to 12 AWG
 Pitch: 5.00 mm
 Env. Prot. Material: **RoHS** Compliant

P	2	3	4	5	6	7	8	9	10	11	12	13
U	5.00	10.00	15.00	20.00	25.00	30.00	35.00	40.00	45.00	50.00	55.00	60.00
V	10.00	15.00	20.00	25.00	30.00	35.00	40.00	45.00	50.00	55.00	60.00	65.00
P	14	15	16	17	18	19	20	21	22	23	24	25
U	65.00	70.00	75.00	80.00	85.00	90.00	95.00	100.00	105.0	110.00	115.00	120.00
V	70.00	75.00	80.00	85.00	90.00	95.00	100.00	105.0	110.00	115.00	120.00	125.00

4	Screw	P	Steel	M2.5 Zn Plated
3	Wire Cage	P	Steel	M2.5 Zn Plated
2	Solder Post	P	Copper	Solder Plated
1	Housing	1	PA66(V2)	Green
Item	Name of Part	Quantity	Material	Notes

End Stackable (Dovetail)
58-112-0 (2 Positions)
58-113-0 (3 Positions)

TITLE			SCALE	
TERMINAL BLOCKS			NTS	
DRAWING NO. 58-112/113				
		UNITS mm		
FILE NAME 58-112&113.pdf		SHEET 1/1		



Mode Electronics Part Number 58-112/113-0