

**Honeywell Sensing and Control**

Search



**11CX12C**  
 ( Home : Products : Switches » MICRO SWITCH™ Hazardous Location Switches » CX )

**narrow your search**

**Products**

- Controls Monitoring and Lighting (286)
- Machine Safety (1727)
- Sensors (6158)
- Switches (9781)
- Wireless (45)

**Technology**

- Control and Instrumentation (890)
- Electromechanical (9303)
- Magnetic (538)
- Platinum thin film (56)
- Thick Film (1372)
- More...

**new products**

**New Wireless Products**

Go farther. Work smarter. Explore new possibilities. Just by cutting the cord and making the switch.



Wireless Web Site  
 WGLA and WPM  
 XYR6000™

[find out more](#)

**white papers**

- Wireless Switches Offer Unlimited Benefit
- Basic Switches Are Not Created Equal
- Applying Precision Switches Sensors for Medical Devices
- New Ways to Measure Torque
- Choosing Safety Switches
- Specifying Hour Meters

**Need help?**

[Click here to contact us](#)



Explosion-Proof Limit Switches Series CX: Short Housing: Side Rotary; Lever not included

**Lever NOT included**

Actual product appearance may vary.  
[click here to download Hi-Res image](#)

[Sales & Service](#) [Distributor Inventory](#)

Overview Specs Documentation Application Notes

**Product Specifications**

Availability	Global
Operating Force (OF)	0,50 Nm [.369 lb ft] max.
Pretravel (PT)	15° max.
Overtravel (OT)	90° min.
Differential Travel (DT)	10° max.
Product Type	MICRO SWITCH™ Weather-Sealed, Explosion-Proof Limit Switches
Actuator	Side Rotary
Lever Type	Lever Not Included - Reference Lever Required Accessory
Circuitry	1NC 1NO SPDT Snap Action; Maintained; 2 Basic Switches
Ampere Rating	15 A Ind./ 0.5 A Res./0.25 A Res.
Supply Voltage	120 Vac, 240 Vac or 480 Vac/125 Vdc/250 Vdc
Housing Material	Aluminum
Termination Type	0.75 in - 14NPT Conduit
Housing Type	CX: Short: 104 mm [4.09 in]
Series Name	CX
Sealing	NEMA 1, 3, 4, 4x, 6, 6P, 7 (Class I, Division 1, Groups C, D), 9 (Class II, Division 1, Groups E, F, G), 13
CSA File #	LR57324
UL File #	E14274
Operating Temperature	-40 °C to 85 °C [-40 °F to 185 °F]
Comment	Maintained with continual CW and/or CCW rotation; Low temperature construction
Agency Approvals and Standards	UL, CSA
UNSPSC Code	302119
UNSPSC Commodity	302119 Switches and controls and relays
Sealed	Explosion-proof

**contacts**

- Customer Service
- Technical Support
- Global Sales & Service
- View Site Demo
- Site Comments?

**meet dr. larry**

**VIDEO** - Dr. Larry Goldstein explains our newest and best technologies.



Meet Dr. Larry

**my links**

- Login to iCOM
- Login to Rep/AD Portal
- Login to Digital University

**News Center**

HONEYWELL INTRODUCES TRUSTABILITY® NSC SERIES, UNCOMPENSATED / UNAMPLIFIED BOARD MOUNT PRESSURE SENSORS

HONEYWELL EXPANDS ITS LIMITLESS™ PLATFORM WITH THE LAUNCH OF ITS GLOBALLY AVAILABLE INDUSTRIAL WIRELESS RECEIVER

HONEYWELL EXTENDS ITS TRUSTABILITY® PRESSURE SENSOR PRODUCT LINE WITH A SINGLE SIDE LIQUID MEDIA OPTION

**MICRO SWITCH Anniversary site**