

Honeywell Sensing and Control

Search

3MS1 00113221
(Home : Products : Sensors » Thermostats » 3MS1 QPL)

narrow your search

Products

- Controls Monitoring and Lighting (352)
- Machine Safety (1727)
- Sensors (5910)
- Switches (9781)
- Wireless (45)

Technology

- Capacitive (26)
- Control and Instrumentation (1054)
- Electromechanical (9307)
- Microstructure (1495)
- Thick Film (1409)
- More...

new products

New Wireless Products

Go farther. Work smarter. Explore new possibilities. Just by cutting the cord and making the switch.



[Wireless Web Site WGLA and WPMM XYR6000™](#)

[find out more](#)

white papers

- ▶ [Wireless Switches Offer Unlimited Benefit](#)
- ▶ [Basic Switches Are Not Created Equal](#)
- ▶ [Applying Precision Switches](#)
- ▶ [Sensors for Medical Devices](#)
- ▶ [New Ways to Measure Torque](#)
- ▶ [Choosing Safety Switches](#)
- ▶ [Specifying Hour Meters](#)

Need help?

[Click here to contact us](#)



3MS1 QPL Series Military Thermostats

Actual product appearance may vary.

[Sales & Service](#)

[Distributor Inventory](#)

Overview **Specs** Documentation Application Notes

Product Specifications

Functional Properties	Close on rise
Reset Type	Automatic
Amperage	5.0 A resistive
Voltage	28 Vac/Vdc
Operating Temperature	-46 °C to 191 °C [-50 °F to 375 °F]
Environmental Exposure Range	-65 °C to 260 °C [-85 °F to 500 °F]
Open Temperature	54.4 °C [130 °F]
Close Temperature	71.1 °C [160 °F]
Open Tolerance	4.4 °C [8 °F]
Close Tolerance	4.4 °C [8 °F]
Dielectric Strength	MIL-STD-202, Method 301; 1250 Vac 60 Hz - Terminal to Case
Insulation Resistance	MIL-STD-202, Method 302; 500 MOhm
Contact Resistance	MIL-STD-202, Method 307; 0.050 Ohm max.
Hermetic Seal	MIL-STD-202, Method 112; Cond. C
Moisture Resistance	MIL-STD-202, Method 106
Shock	MIL-STD-202, Method 213; 100 G
Vibration	MIL-STD-202, Method 204; 20 G
Acceleration	MIL-STD-202, Method 212; 20 G
Thermal Shock	MIL-STD-202, Method 107; Cond. B
Salt Spray	MIL-STD-202, Method 101; Cond. B
Housing Material	Steel housing hermetically sealed with glass-to-metal seal at terminal junction
Contact Material	Consil alloy MG/silver
Agency Approvals and Standards	Mil-PRF-24236/1 and QPL
Mounting	B209 fixed bracket
Series Name	3MS1 QPL

contacts

- ▶ [Customer Service](#)
- ▶ [Technical Support](#)
- ▶ [Global Sales & Service](#)
- ▶ [View Site Demo](#)
- ▶ [Site Comments?](#)

meet dr. larry

VIDEO - Dr. Larry Goldstein explains our newest and best technologies.



▶ [Meet Dr. Larry](#)

my links

- ▶ [Login to iCOM](#)
- ▶ [Login to Rep/AD Portal](#)
- ▶ [Login to Digital University](#)

News Center

- ▶ [HONEYWELL EXTENDS ITS TRUSTABILITY® PRESSURE SENSOR PRODUCT LINE WITH A SINGLE SIDE LIQUID MEDIA OPTION](#)
- ▶ [HONEYWELL ADDS NEW 100° AND 180° ARC CONFIGURATIONS TO ITS SMART POSITION SENSOR PORTFOLIO](#)
- ▶ [HONEYWELL INTRODUCES ITS HAWK™ RESOLVERS 1-INCH SERIES, FULLY HOUSED CONFIGURATION](#)
- ▶ [HONEYWELL INTRODUCES MICROPOWER OMNIPOLAR DIGITAL HALL-EFFECT SENSOR ICS WITH LOW SUPPLY VOLTAGE AND ULTRA LOW TYPICAL CURRENT](#)

MICRO SWITCH Anniversary site



