

## Honeywell Sensing and Control

Search



### narrow your search

#### Products

- Controls Monitoring and Lighting (286)
- Machine Safety (1727)
- Sensors (6165)
- Switches (9781)
- Wireless (45)

#### Technology

- Control and Instrumentation (890)
- Electromechanical (9307)
- Magnetic (541)
- Platinum thin film (56)
- Thick Film (1372)
- More...

### new products

#### New Wireless Products

Go farther. Work smarter. Explore new possibilities. Just by cutting the cord and making the switch.



Wireless Web Site  
WGLA and WPMM  
XYR6000™

[find out more](#)

### white papers

- Wireless Switches Offer Unlimited Benefit
- Basic Switches Are Not Created Equal
- Applying Precision Switches
- Sensors for Medical Devices
- New Ways to Measure Torque
- Choosing Safety Switches
- Specifying Hour Meters

### Need help?

[Click here to contact us](#)

### 914CE18-15A

( Home : Products : Switches » MICRO SWITCH™ Limit Switches » MICRO SWITCH™ Medium-Duty Limit Switches » 914CE )



Actual product appearance may vary.

Miniature Enclosed Switches Series 914CE: Top Plunger; 1NC 1NO SPDT Snap Action; 15 foot Cable

[Sales & Service](#) [Distributor Inventory](#)

[Overview](#) [Specs](#) [Documentation](#) [Application Notes](#)

#### Product Specifications

|                                |  |
|--------------------------------|--|
| Availability                   | Global   |
| Operating Force (OF)           | 22.5 N [5.06 lb] max.                                |
| Release Force                  | 4,4 N [0.99 lb] max.                                 |
| Pretravel (PT)                 | 1,0 mm ±0,5 mm [0.04 in ±0.02 in]                    |
| Overtravel (OT)                | 3,0 mm [0.118 in] min.                               |
| Differential Travel (DT)       | 0,1 mm [0.004 in] max.                               |
| Product Type                   | MICRO SWITCH™ Miniature Limit Switches               |
| Actuator                       | Top Plunger  |
| Lever Type                     | None   |
| Circuitry                      | 1NC 1NO SPDT Snap Action                             |
| Ampere Rating                  | 5 A (Thermal)  |
| Supply Voltage                 | 240 Vac  |
| Housing Material               | Zinc Die-Cast  |
| Termination Type               | 15 foot Cable  |
| Series Name                    | 914CE  |
| Sealing                        | IP66, IP67, IP68; NEMA 1, 2, 3, 3R, 4, 6, 6P, 12, 13 |
| UL File #                      | E41859   |
| Expected Mechanical Life       | up to 10 Million                                     |
| Operating Temperature          | 0 °C to 70 °C [35 °F to 160 °F]                      |
| Comment                        | Side Exit Cable; With Boot Seal                      |
| Agency Approvals and Standards | UL, CE, CSA, IEC947-5-1, EN60947-5-1                 |
| UNSPSC Code                    | 302119   |
| UNSPSC Commodity               | 302119 Switches and controls and relays              |
| Sealed                         | Industrial   |

### contacts

- Customer Service
- Technical Support
- Global Sales & Service
- View Site Demo
- Site Comments?

### meet dr. larry

VIDEO - Dr. Larry Goldstein explains our newest and best technologies.



Meet Dr. Larry

### my links

- Login to iCOM
- Login to Rep/AD Portal
- Login to Digital University

### News Center

- Honeywell Introduces TruStability® NSC Series, Uncompensated / Unamplified Board Mount Pressure Sensors
- HONEYWELL EXPANDS ITS LIMITLESS™ PLATFORM WITH THE LAUNCH OF ITS GLOBALLY AVAILABLE INDUSTRIAL WIRELESS RECEIVER
- HONEYWELL EXTENDS ITS TRUSTABILITY® PRESSURE SENSOR PRODUCT LINE WITH A SINGLE SIDE LIQUID MEDIA OPTION
- HONEYWELL ADDS NEW 100° AND 180° ARC CONFIGURATIONS TO ITS SMART POSITION SENSOR PORTFOLIO
- HONEYWELL INTRODUCES ITS HAWK™ RESOLVERS 1-INCH SERIES, FULLY HOUSED CONFIGURATION
- HONEYWELL INTRODUCES MICROPOWER OMNIPOLAR DIGITAL HALL-EFFECT SENSOR ICS WITH LOW SUPPLY VOLTAGE AND ULTRA LOW TYPICAL CURRENT

[MICRO SWITCH Anniversary site](#)