

**NEUTRIK**[Products](#) > [Audio](#) > [XLR](#) > [XLR Cable Connectors](#) > [RX Series](#) > NC7MRX-B[print](#)

# NC7MRX-B

The RX Series is the right angle version of the XX cable connector series. The successor of the RC series offers several new features which make it more reliable, easier to assemble and improves contact integrity as well cable strain relief.

7 pole right angle male cable connector, black metal housing, gold contacts

## Features & Benefits

- Extra slim right-angle connector
- 7 selectable cable outlet positions
- Male connector with improved locking recess without "window", more stringent housing increases durability
- Improved chuck type strain relief provides higher pull-out force and makes assembly easier and faster
- Boot with polyurethane gland gives high protection to cable bending stresses
- Coloured rings and boots available for coding or identification
- Sleek and ergonomic design - valuable and handy
- Branded with unique hologram - guarantees genuine and authentic Neutrik product




## Downloads

- [Assembly Instruction - XLR RX Series](#)
- [Product Guide 2012, 02 XLR](#)
- [UL Certificate of Compliance](#)
- [Drawing NC7MRX](#)
- [Drawing NC7MRX](#)

## Links

- [UL Certificate \(ECBT2.E135070\)](#)
- [cUL Certificate \(ECBT8.E135070\)](#)

## Outlet Positions



Technical Information [hide](#)

Product	
Title	NC7MRX-B
Connection Type	XLR
Gender	male
Electrical	
Capacitance between contacts	$\leq 9$ pF
Contact resistance	$\leq 3$ m $\Omega$ (inner)
Dielectric strength	1,5 kVdc
Insulation resistance	$> 2$ G $\Omega$ (initial)
Rated current per contact	5 A
Rated voltage	50 V
Mechanical	
Cabel O.D.	3.5 - 8.0 mm
Insertion force	$\leq 20$ N
Withdrawal force	$\leq 20$ N
Lifetime	$> 1000$ mating cycles
Wiresize	max. 1.0 mm <sup>2</sup>
Wiresize	max. 18 AWG
Wiring	Solder contacts
Locking device	Latch lock
Material	
Boot	Polyurethan
Contact plating	0.2 $\mu$ m Au hard alloy over 2 $\mu$ m Ni
Contacts	Brass (CuZn39Pb3)
Insert	Polyamide (PA 6.6 30 % GR)
Locking element	Zinc diecast (ZnAl4Cu1)
Shell	Zinc diecast (ZnAl4Cu1)
Shell plating	Black chromium
Strain relief	Polyacetal (POM)
Environmental	

Flammability	UL 94 HB
Standard compliance	IEC 61076-2-103
Protection class	IP 40
Solderability	Complies with IEC 68-2-20
Temperature range	-30 °C to +80 °C

## Accessories



BXX-\*




BXX-CR



BXX-14



HTXP



XXR-\*



XXCR

