

Screw termination block - CT-TERMIBLOCK 10 DA - 0441711

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Screw termination block with disconnect contacts for accommodating protective plugs CT and CTM. Use in MCR and telecommunications systems. Design: 10 double wires

Product Features

- For COMTRAB protective plugs
- Automatically closing feed-through/disconnect contacts
- Ground terminal blocks on both sides with plug-in connection for the protective plugs used
- Mounting on DIN rails according to EN 60715



Key Commercial Data

| | |
|--------------------------------------|---|
| Packing unit | 1 pc |
| GTIN |  4 017918 002213 |
| Weight per Piece (excluding packing) | 185.4 g |
| Custom tariff number | 85369010 |
| Country of origin | Germany |

Technical data

Environmental Product Compliance

| | |
|------------|----------------------------|
| REACH SVHC | 4-Nonylphenol, ethoxylated |
|------------|----------------------------|

Dimensions

| | |
|--------|---------|
| Height | 43 mm |
| Width | 118 mm |
| Depth | 40.9 mm |

Ambient conditions

Screw termination block - CT-TERMIBLOCK 10 DA - 0441711

Technical data

Ambient conditions

| | |
|---------------------------------|------------------|
| Ambient temperature (operation) | -40 °C ... 85 °C |
| Degree of protection | IP20 |

General

| | |
|---|-----------------|
| Housing material | PA |
| Flammability rating according to UL 94 | V2 |
| Color | black |
| Standards for clearances and creepage distances | IEC 60664-1 |
| Overvoltage category | III |
| Degree of pollution | 3 |
| Mounting type | DIN rail: 35 mm |
| Type | LSA-PLUS module |

Protective circuit

| | |
|--|----------|
| Maximum continuous voltage U_C (wire-wire) | 240 V AC |
| Maximum continuous voltage U_C (wire-ground) | 250 V AC |
| Operating effective current I_C at U_C | 5 A |

Connection data

| | |
|---------------------------------------|-----------------------|
| Connection method | Screw terminal blocks |
| Connection type IN | Screw terminal blocks |
| Connection type OUT | Screw terminal blocks |
| Screw thread | M3 |
| Tightening torque | 0.5 Nm |
| Stripping length | 7 mm |
| Conductor cross section flexible min. | 0.2 mm ² |
| Conductor cross section flexible max. | 2.5 mm ² |
| Conductor cross section solid min. | 0.2 mm ² |
| Conductor cross section solid max. | 2.5 mm ² |
| Conductor cross section AWG min. | 24 |
| Conductor cross section AWG max. | 14 |

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 27140201 |
| eCl@ss 4.1 | 27130801 |
| eCl@ss 5.0 | 27130801 |
| eCl@ss 5.1 | 27130801 |

Screw termination block - CT-TERMIBLOCK 10 DA - 0441711

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 6.0 | 27130807 |
| eCl@ss 7.0 | 27130807 |
| eCl@ss 8.0 | 27440315 |

ETIM

| | |
|----------|----------|
| ETIM 2.0 | EC000943 |
| ETIM 3.0 | EC000943 |
| ETIM 4.0 | EC000371 |
| ETIM 5.0 | EC000371 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 30212010 |
| UNSPSC 7.0901 | 39121610 |
| UNSPSC 11 | 39121610 |
| UNSPSC 12.01 | 39121610 |
| UNSPSC 13.2 | 39121620 |

Approvals

Approvals


Approvals

UL Listed / EAC / EAC

Ex Approvals

Approvals submitted

Approval details

| |
|---|
| UL Listed  |
|---|

| |
|-----|
| EAC |
|-----|

Screw termination block - CT-TERMIBLOCK 10 DA - 0441711

Approvals

EAC

Drawings

Dimensional drawing

