

Insert label - PABE-S - 1013180


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Insert label, white, unlabeled, Horizontal: Symbols, Mounting type: Insert, Lettering field: 4 x 2.1 mm

The illustration shows a combination of versions PABE-B, PABE-Z and PABE-AZ

Key Commercial Data

Packing unit	1 pc
Minimum order quantity	10 pc
GTIN	 4 017918 013608
Weight per Piece (excluding packing)	3.53 g
Custom tariff number	39269097
Country of origin	Italy

Technical data

Dimensions

Width (a)	2.1 mm
Cable diameter	> 0 mm

Ambient conditions

Ambient temperature (operation)	-50 °C ... 80 °C
---------------------------------	------------------

General

Note	Required marking is to be specified when ordering.
	Please use the order key when ordering.
Color	white
Base element material	PVC
Components	Silicone-free
Flammability rating according to UL 94	V0
Material	PVC

Insert label - PABE-S - 1013180

Technical data

General

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
Printing direction	Horizontal
Printing	Symbols
Number of individual labels	24
Marking mounting type	Insert

Standards and Regulations

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
Flammability rating according to UL 94	V0

Classifications

eCl@ss

eCl@ss 4.0	24190219
eCl@ss 4.1	24190219
eCl@ss 5.0	27149103
eCl@ss 5.1	27400401
eCl@ss 6.0	27149103
eCl@ss 7.0	27400401
eCl@ss 8.0	27149129

ETIM

ETIM 2.0	EC000761
ETIM 3.0	EC000761
ETIM 4.0	EC001530
ETIM 5.0	EC001288

UNSPSC

UNSPSC 6.01	30211811
UNSPSC 7.0901	39121410
UNSPSC 11	39121410
UNSPSC 12.01	39121410
UNSPSC 13.2	39121410