

Cable reel - SAC-3P-22AWG-OE-OE-542-300,0US - 1421997

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



By the meter, Cable reel, PVC, yellow, 3-wire, Color, single wire: brown, blue, black, Cable length: 300 m



Key Commercial Data

Packing unit	1 STK
GTIN	 4 055626 324623
GTIN	4055626324623
Custom tariff number	85444290
Country of origin	United States

Technical data

Dimensions

Length of cable	300 m
-----------------	-------

General

Number of positions	3
---------------------	---

Cable

Cable type	PVC yellow 105 °C
Cable type (abbreviation)	542
UL AWM style	2517 (105 °C / 300 V)
AWG signal line	22
Core diameter including insulation	1.27 mm ±0.03 mm
Wire colors	brown, blue, black
Overall twist	3 wires, twisted

Cable reel - SAC-3P-22AWG-OE-OE-542-300,0US - 1421997


Technical data

Cable

External sheath, color	yellow
External cable diameter D	4.7 mm ±0.2 mm
Minimum bending radius, flexible installation	8 x D
Cable weight	30 kg/km
Outer sheath, material	PVC
Material conductor insulation	PVC
Conductor material	Tin-plated Cu litz wires
Insulation resistance	≥ (550 M Ohms/m @ 500V)
Conductor resistance	max. 50.5 Ω/km (20° C)
Nominal voltage, cable	300 V
Special properties	UL standards PLTC and ITC
Flame resistance	FT4
Other resistance	UV resistant
Ambient temperature (operation)	-30 °C ... 105 °C (cable, fixed installation)

Drawings

Cable cross section



PVC yellow 105 °C [542]

Classifications

eCl@ss

eCl@ss 5.1	27061801
eCl@ss 6.0	27061801
eCl@ss 8.0	27060307
eCl@ss 9.0	27060307

ETIM

ETIM 5.0	EC000830
----------	----------

Cable reel - SAC-3P-22AWG-OE-OE-542-300,0US - 1421997

Classifications

UNSPSC

UNSPSC 13.2	43211617
-------------	----------

Accessories

Accessories

Stripping tool

Stripping tool - WIREFOX SAC - 1212623



Stripping pliers, for halogen-free sensor/actuator cables (SAC cables), with PUR and PVC insulation, from Ø of 4.4 to 7 mm, any stripping length