

## Cable gland - HC-M-KV-M40(27-34) - 1607729

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)




Metal screw connection up to 5 bar, thread length: 8 mm, cable diameter: 27 ... 34 mm, WAF 50, screw connection: M40

The illustration shows version HC-M-KV-M20



### Key commercial data

Packing unit	1 pc
GTIN	 4 017918 938819
Weight per Piece (excluding packing)	169.5 GRM
Custom tariff number	74199990
Country of origin	Germany

### Technical data

#### Dimensions

Wrench size, union nut	50 mm
Wrench size, support	50 mm
Length of the connecting thread	8 mm
External cable diameter	27 mm ... 34 mm
Conductor sealing range	27.00 mm ... 34.00 mm

#### Ambient conditions

Degree of protection	IP68, to 5 bar
	IP68 (Up to 5 bar)
Ambient temperature (operation)	-20 °C ... 100 °C

#### General

Type of the screw connection	M40
------------------------------	-----

## Cable gland - HC-M-KV-M40(27-34) - 1607729

### Technical data

#### General

Cable gland material	Nickel-plated brass
Seal material	Neoprene
Cable seal material	Neoprene
Material, O-ring	NBR
Thread type on connection side	M40
Tightening torque, union nut	20.00 Nm

### Classifications

#### eCl@ss

eCl@ss 4.0	27141209
eCl@ss 4.1	27141209
eCl@ss 5.0	27149109
eCl@ss 5.1	27149109
eCl@ss 6.0	27149109
eCl@ss 7.0	27149109
eCl@ss 8.0	27149109

#### ETIM

ETIM 2.0	EC000441
ETIM 3.0	EC000441
ETIM 4.0	EC000441
ETIM 5.0	EC000441

#### UNSPSC

UNSPSC 6.01	31261502
UNSPSC 7.0901	31261502
UNSPSC 11	31261502
UNSPSC 12.01	31261502
UNSPSC 13.2	31261502

### Drawings

Dimensioned drawing

Dimensional drawing

