

Fuse plug - PV-C-M/F-PRO/F-1000/30-EU - 1622159

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Fuse connector for protecting modules and devices in photovoltaic systems, black, SUNCLIX pin connector pattern, 1000 V/30 A, IP68 (24 h/2 m)

SUNCLIX fuse connector, in the version for 1000 V system voltage


Product Description

SUNCLIX fuse connector, for 1000 V system voltage, fuse-link nominal current of 30 A, EU version

Why buy this product

- One-piece design
- Robust, easy-to-install fuse element for outdoor use
- High-quality fuse-link
- Degree of protection: IP68 (24 h/2 m)
-
- 1000 V (EN)

Key Commercial Data

Packing unit	1 STK
Minimum order quantity	8 STK
GTIN	 4 055626 130590
GTIN	4055626130590
Weight per Piece (excluding packing)	55.000 g
Custom tariff number	85363030
Country of origin	Germany

Technical data

Ambient conditions

Fuse plug - PV-C-M/F-PRO/F-1000/30-EU - 1622159

Technical data

Ambient conditions

Degree of protection (when plugged in)	IP66 / IP68 (2 m / 24 h)
Ambient temperature (operation)	-40 °C ... 50 °C

General

Rated voltage	1000 V
Fuse-link nominal current	28 A DC (Nominal current of the fuse-link)
Fuse adapter nominal current	28 A DC

Material

Flammability rating according to UL 94	V0
--	----

Standards and Regulations


Flammability rating according to UL 94	V0
--	----

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Drawings

Dimensional drawing



Classifications

eCl@ss

eCl@ss 5.1	27260702
eCl@ss 8.0	27440102
eCl@ss 9.0	27440107

ETIM

ETIM 5.0	EC002635
ETIM 6.0	EC002635

Fuse plug - PV-C-M/F-PRO/F-1000/30-EU - 1622159

Classifications

UNSPSC

UNSPSC 13.2	39121409
-------------	----------

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC		B.01742
-----	---	---------
