


## Printed-circuit board connector - MSTBT 2,5/ 4-ST OG - 1714271

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Plug component, Nominal current: 12 A, Rated voltage (III/2): 320 V, Number of positions: 4, Pitch: 5 mm, Connection method: Screw connection with tension sleeve, Color: orange, Contact surface: Tin



### Key Commercial Data

Packing unit	1
GTIN	 4 055626 348377
GTIN	4055626348377
Custom tariff number	85366990

### Technical data

#### Dimensions

Width	20.00 mm
Pitch	5 mm
Dimension a	15.00 mm

#### General

Number of positions	4
Connection method	Screw connection with tension sleeve
Insulating material group	I
Rated voltage (III/2)	320 V
Nominal current I <sub>N</sub>	12 A
Flammability rating according to UL 94	V0
Screw thread	M3

#### Standards and Regulations

Flammability rating according to UL 94	V0
--	----

#### Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50
------------	--

## Printed-circuit board connector - MSTBT 2,5/ 4-ST OG - 1714271

### Technical data

#### Environmental Product Compliance

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"
---