

Component housing - HS LC-H-D2/ R4XC10-2,54 - 2202323


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Fiber optics can be used for the ME, ME-MAX, ME-IO, ME PLC, and EH housing ranges (housing must be processed), Color: transparent



Key Commercial Data

Packing unit	1 STK
Minimum order quantity	100 STK
GTIN	 4 055626 050249
GTIN	4055626050249
Weight per Piece (excluding packing)	3.000 g
Custom tariff number	39269097
Country of origin	Tunisia

Technical data

General

Housing type	Fiber optics
Housing material	PC
Color	transparent

Ambient conditions

Ambient temperature (operation)	-40 °C ... 85 °C
---------------------------------	------------------

Dimensions

Pitch	2.54 mm
-------	---------

Technical data

Flammability rating according to UL 94	HB
--	----

Component housing - HS LC-H-D2/ R4XC10-2,54 - 2202323

Technical data

Technical data

Number of positions	40
---------------------	----

Standards and Regulations


Flammability rating according to UL 94	HB
--	----

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Drawings

Dimensional drawing



Details on positioning inside the electronics housing can be found in the download area under "Design-In"