

Membrane keypad - KP HCS T-MED K28 C4 P13 - 2203570


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Membrane keypad, self-adhesive, silver conduction technology, 28 keys, embossed, 4 colors, connection cable: 124 mm, with crimp female connector RM 2.54 mm, operating temperature -20 °C ... 70 °C

RoHS

Key Commercial Data

Packing unit	1 pc
GTIN	 4 055626 474038
GTIN	4055626474038
Weight per Piece (excluding packing)	20.000 g
Custom tariff number	85371098
Country of origin	Germany

Technical data

Product properties

Type	KP HCS T-MED K28 C4 P13
Order No.	2203570
Mounting type	adhesive
Number of positions	13
Number of keys	28 (4 x 7)
Number of colors	4
Number of socket pins	13
Technology	Conductive silver technology
Embossing	Dome embossing 11 x 11 mm

Dimensions

Dimensions	64 mm x 116 mm
------------	----------------

Membrane keypad - KP HCS T-MED K28 C4 P13 - 2203570

Technical data

Dimensions

Pitch	2.54 mm
Length	124 mm (Membrane cable)

Ambient conditions

Ambient temperature (storage/transport)	-20 °C ... 70 °C
Ambient temperature (operation)	-40 °C ... 80 °C

Packaging details

Pieces per package	1
Denomination packing units	Pcs.

Classifications

eCl@ss

eCl@ss 10.0.1	27182702
eCl@ss 5.1	27180506
eCl@ss 6.0	27180800
eCl@ss 7.0	27182702
eCl@ss 8.0	27182702
eCl@ss 9.0	27182702

ETIM

ETIM 5.0	EC001031
ETIM 6.0	EC001031
ETIM 7.0	EC001031

Accessories

Additional products

Electronic housing - HCS-T MEDIUM 1W C 1 1 7035 - 2203138



Handheld housing, T-Medium, light gray, consisting of two half shells, two front plates with screws, front 1.1 mm recessed, with window and keypad slot

Membrane keypad - KP HCS T-MED K28 C4 P13 - 2203570

Accessories

Electronic housing - HCS-T MEDIUM 1W C C 1 7035 - 2203139



Handheld housing, T-Medium, light gray, consisting of two half shells, front plates below with screws, front 1.1 mm recessed, with window and keypad slot