

Cable - FLK 50/EZ-DR/ 50/KONFEK/S - 2299097

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Assembled shielded round cable; connection 1: IDC/FLK socket strip (1x 50-position); connection 2: IDC/FLK socket strip (1x 50-position) (The braided shield is routed to a separate cable end.); cable length: 0.5 m



Key Commercial Data

| | |
|--------------------------------------|---|
| Packing unit | 1 STK |
| GTIN |  4 017918 832230 |
| GTIN | 4017918832230 |
| Weight per Piece (excluding packing) | 110.300 g |
| Custom tariff number | 85444290 |
| Country of origin | Germany |

Technical data

General

| | |
|---|---|
| Nominal voltage U_N | < 50 V AC |
| | 60 V DC |
| Max. current carrying capacity per path | 1 A |
| Max. conductor resistance | 0.16 Ω /m |
| Length of cable | 0.5 m |
| Single wire, cross section | 0.14 mm ² |
| Single wire, cross section [AWG] | 26 |
| Conductor construction: Number of litz wires: | 7 |
| Single wire, material | Cu tin-plated |
| External diameter | 11 mm |
| Cable, preassembly | Insulation displacement, IEC 60352-4/DIN EN 60352-4 |

Cable - FLK 50/EZ-DR/ 50/KONFEK/S - 2299097

Technical data

General

| | |
|-----------|--|
| Shielding | yes |
| | Tinned copper-braided shield, approx. 85% covering |

Environmental conditions

| | |
|---|------------------|
| Ambient temperature (operation) | -20 °C ... 50 °C |
| Ambient temperature (storage/transport) | -20 °C ... 70 °C |
| Flame resistance | IEC 60332-3-22 |

Connector 1

| | |
|-----------------------|--|
| Connection name | Field level |
| Connection method | IDC/FLK socket strip |
| Number of connections | 1 |
| Number of positions | 50 |
| Note | The braided shield is routed to a separate cable end. The separate cable end is approximately 0.5 m long (H05V-K 1 mm ² , black) |
| Pitch | 2.54 mm |

Connector 2

| | |
|-----------------------|----------------------|
| Connection name | Controller level |
| Connection method | IDC/FLK socket strip |
| Number of connections | 1 |
| Number of positions | 50 |
| Pitch | 2.54 mm |

Supported controller

| | |
|---------------------|---------------------------|
| Controller | SIEMENS S7-300 / ET 200 M |
| - suitable I/O card | CPU 313C-2DP |
| | CPU 314C-2PtP |
| | 6ES7 321-1BL00-0AA0 |
| | 6ES7 322-1BL00-0AA0 |
| | 6ES7 323-1BL00-0AA0 |
| | 6ES7 331-7NF00-0AB0 |
| | 6ES7 331-7PF01-0AB0 |
| | 6ES7 331-7PF11-0AB0 |
| | 6ES7 350-2AH01-0AE0 |
| | 6ES7 357-4AH01-0AE0 |
| | CPU 314C-2DP |
| | 6ES7 332-5HF00-0AB0 |
| | 6ES7 331-7NF10-0AB0 |

Cable - FLK 50/EZ-DR/ 50/KONFEK/S - 2299097

Technical data

Supported controller

| | |
|---------------------|--|
| | 6ES7 331-1KF01-0AB0 |
| | CPU 313C |
| | CPU 313C-2PiP |
| Controller | SIEMENS S7-400 |
| - suitable I/O card | 6ES7 421-1BL01-0AA0 |
| | 6ES7 421-7BH01-0AB0 |
| | 6ES7 421-7DH00-0AA0 |
| | 6ES7 422-1BL00-0AA0 |
| | 6ES7 422-7BL00-0AB0 |
| | 6ES7 431-0HH0-0AB0 |
| | 6ES7 431-1KF00-0AB0 |
| | 6ES7 431-1KF10-0AB0 |
| | 6ES7 431-1KF20-0AB0 |
| | 6ES7 431-7KF00-0AB0 |
| | 6ES7 431-7KF10-0AB0 |
| | 6ES7 431-7QH00-0AB0 |
| | 6ES7 432-1HF00-0AB0 |
| Controller | Schneider Electric Modicon TSX QUANTUM |
| - suitable I/O card | DDI 353 |
| | DDI 841 |
| | DDI 853 |
| | DAI 340 |
| | DAI 353 |
| | DAI 440 |
| | DAI 453 |
| | DDO 353 |
| | DDM 390 |
| | ACI 030 |
| | ACI 040 |
| | ATI 030 |
| | ARI 030 |
| | AVI 030 |
| | ACO 020 |
| | ACO 130 |
| | AVO 020 |
| | EHC 105 |
| | EHC 202 |

Cable - FLK 50/EZ-DR/ 50/KONFEK/S - 2299097

Technical data

Supported controller

| | |
|---------------------|-----------------------------|
| Controller | ALLEN-BRADLEY ControlLogix |
| - suitable I/O card | 1756-IA16I |
| | 1756-IB16D |
| | 1756-IB16I |
| | 1756-IB32 |
| | 1756-IH16I |
| | 1756-OB32 |
| | 1756-IF8 |
| | 1756-IF16 |
| | 1756-HSC |
| | 1756-M02AE |
| Controller | ALLEN-BRADLEY PLC 5 |
| - suitable I/O card | 1771 IBN |
| | 1771 OBN |
| Controller | HONEYWELL Experion PKS C200 |
| - suitable I/O card | TC-IDK 161 |
| | TC-IDX 161 |
| | TC-IDJ 161 |
| | TC-IDD 321 |
| | TC-ODD 321 |
| | TC-IAH 161 |
| Controller | ALLEN-BRADLEY SLC 500 |
| - suitable I/O card | 1746 OA16 |
| | 1746 OW16 |

Standards and Regulations

| | |
|------------------|----------------|
| Flame resistance | IEC 60332-3-22 |
|------------------|----------------|

Color code

| | |
|---|--|
| Connector 1 = connector 2 (optional) = wire color | IDC/FLK50 (1) = IDC/FLK50 (1) = black |
| | IDC/FLK50 (2) = IDC/FLK50 (2) = brown |
| | IDC/FLK50 (3) = IDC/FLK50 (3) = red |
| | IDC/FLK50 (4) = IDC/FLK50 (4) = orange |
| | IDC/FLK50 (5) = IDC/FLK50 (5) = yellow |
| | IDC/FLK50 (6) = IDC/FLK50 (6) = green |
| | IDC/FLK50 (7) = IDC/FLK50 (7) = blue |
| | IDC/FLK50 (8) = IDC/FLK50 (8) = violet |
| | IDC/FLK50 (9) = IDC/FLK50 (9) = gray |

Cable - FLK 50/EZ-DR/ 50/KONFEK/S - 2299097

Technical data

Color code

| | |
|--|---|
| | IDC/FLK50 (10) = IDC/FLK50 (10) = white |
| | IDC/FLK50 (11) = IDC/FLK50 (11) = white-black |
| | IDC/FLK50 (12) = IDC/FLK50 (12) = white-brown |
| | IDC/FLK50 (13) = IDC/FLK50 (13) = white-red |
| | IDC/FLK50 (14) = IDC/FLK50 (14) = white-orange |
| | IDC/FLK50 (15) = IDC/FLK50 (15) = white-yellow |
| | IDC/FLK50 (16) = IDC/FLK50 (16) = white-green |
| | IDC/FLK50 (17) = IDC/FLK50 (17) = white-blue |
| | IDC/FLK50 (18) = IDC/FLK50 (18) = white-violet |
| | IDC/FLK50 (19) = IDC/FLK50 (19) = white-gray |
| | IDC/FLK50 (20) = IDC/FLK50 (20) = brown-black |
| | IDC/FLK50 (21) = IDC/FLK50 (21) = brown-red |
| | IDC/FLK50 (22) = IDC/FLK50 (22) = brown-orange |
| | IDC/FLK50 (23) = IDC/FLK50 (23) = brown-yellow |
| | IDC/FLK50 (24) = IDC/FLK50 (24) = brown-green |
| | IDC/FLK50 (25) = IDC/FLK50 (25) = brown-blue |
| | IDC/FLK50 (26) = IDC/FLK50 (26) = brown-violet |
| | IDC/FLK50 (27) = IDC/FLK50 (27) = brown-gray |
| | IDC/FLK50 (28) = IDC/FLK50 (28) = brown-white |
| | IDC/FLK50 (29) = IDC/FLK50 (29) = green-black |
| | IDC/FLK50 (30) = IDC/FLK50 (30) = green-brown |
| | IDC/FLK50 (31) = IDC/FLK50 (31) = green-red |
| | IDC/FLK50 (32) = IDC/FLK50 (32) = green-orange |
| | IDC/FLK50 (33) = IDC/FLK50 (33) = green-blue |
| | IDC/FLK50 (34) = IDC/FLK50 (34) = green-violet |
| | IDC/FLK50 (35) = IDC/FLK50 (35) = green-gray |
| | IDC/FLK50 (36) = IDC/FLK50 (36) = green-white |
| | IDC/FLK50 (37) = IDC/FLK50 (37) = yellow-black |
| | IDC/FLK50 (38) = IDC/FLK50 (38) = yellow-brown |
| | IDC/FLK50 (39) = IDC/FLK50 (39) = yellow-red |
| | IDC/FLK50 (40) = IDC/FLK50 (40) = yellow-orange |
| | IDC/FLK50 (41) = IDC/FLK50 (41) = yellow-blue |
| | IDC/FLK50 (42) = IDC/FLK50 (42) = yellow-violet |
| | IDC/FLK50 (43) = IDC/FLK50 (43) = yellow-gray |
| | IDC/FLK50 (44) = IDC/FLK50 (44) = yellow-white |
| | IDC/FLK50 (45) = IDC/FLK50 (45) = gray-black |
| | IDC/FLK50 (46) = IDC/FLK50 (46) = gray-brown |

Cable - FLK 50/EZ-DR/ 50/KONFEK/S - 2299097

Technical data

Color code

| | |
|--|---|
| | IDC/FLK50 (47) = IDC/FLK50 (47) = gray-red |
| | IDC/FLK50 (48) = IDC/FLK50 (48) = gray-orange |
| | IDC/FLK50 (49) = IDC/FLK50 (49) = gray-yellow |
| | IDC/FLK50 (50) = IDC/FLK50 (50) = gray-green |

Environmental Product Compliance

| | |
|------------|---|
| China RoHS | Environmentally Friendly Use Period = 50 |
| | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 5.1 | 27249205 |
| eCl@ss 6.0 | 27249205 |
| eCl@ss 7.0 | 27249205 |
| eCl@ss 8.0 | 27249205 |
| eCl@ss 9.0 | 27242220 |

ETIM

| | |
|----------|----------|
| ETIM 2.0 | EC000237 |
| ETIM 3.0 | EC000237 |
| ETIM 4.0 | EC000237 |
| ETIM 5.0 | EC000237 |
| ETIM 6.0 | EC000237 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 26121620 |
| UNSPSC 7.0901 | 26121620 |
| UNSPSC 11 | 26121620 |
| UNSPSC 12.01 | 26121620 |
| UNSPSC 13.2 | 26121620 |

Approvals

Approvals

Approvals

EAC / EAC / UL Listed / cUL Listed / cULus Listed

Cable - FLK 50/EZ-DR/ 50/KONFEK/S - 2299097

Approvals

Ex Approvals

Approval details

| | | |
|-----|--|---------------|
| EAC | | EAC-Zulassung |
|-----|--|---------------|

| | | |
|-----|--|---------------------|
| EAC | | RU C-DE.A*30.B00767 |
|-----|--|---------------------|

| | | | |
|-----------|--|---|---------------|
| UL Listed | | http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm | FILE E 238705 |
| | | Nominal current IN | 1 A |
| | | Nominal voltage UN | 125 V |

| | | | |
|------------|--|---|---------------|
| cUL Listed | | http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm | FILE E 238705 |
| | | Nominal current IN | 1 A |
| | | Nominal voltage UN | 125 V |

| | | | |
|--------------|--|--|--|
| cULus Listed | | | |
|--------------|--|--|--|

Accessories

Accessories

Marker carrier cable

Cable - FLK 50/EZ-DR/ 50/KONFEK/S - 2299097

Accessories

Cable marker carrier - KME - 0807083



Cable marker carrier, white, unlabeled, mounting type: Assembly with cable binders, cable diameter: > 5 mm, lettering field size: 20 mm x 8 mm