

Interface module - UM 45-MKDS/MDSTBW/ 8SI/SO262 - 2319443


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Fuse module, with screw connection, COMBICON connectors with stand-off and encoding against incorrect connection, for mounting on NS 35/7,5 or NS 32



Key Commercial Data

Packing unit	1 pc
Minimum order quantity	50 pc
GTIN	 4 046356 364898
GTIN	4046356364898
Weight per Piece (excluding packing)	300.000 g
Custom tariff number	85369010
Country of origin	Germany

Technical data

Dimensions

Width	48.5 mm
Height	45 mm
Depth	160 mm

Ambient conditions

Ambient temperature (operation)	-20 °C ... 50 °C
Maximum altitude	max. 2000 m
Degree of protection	IP20
	≥ IP54 (Installation location)

General

Interface module - UM 45-MKDS/MDSTBW/ 8SI/SO262 - 2319443

Technical data

General

Nominal voltage U_N	230 V AC
Max. perm. current (per branch)	2 A
Mounting position	any

Connection data

Connection name	PCB connection
Connection method	Screw connection
Stripping length	7 mm
Screw thread	M3
Number of positions	8
Conductor cross section solid	0.14 mm ² ... 2.5 mm ²
Conductor cross section flexible	0.14 mm ² ... 1.5 mm ²
Conductor cross section AWG	26 ... 14

Connection data 2

Connection name	COMBICON connection
Connection method	Screw connection
Conductor cross section solid	0.2 mm ² ... 2.5 mm ²
Conductor cross section flexible	0.2 mm ² ... 2.5 mm ²
Conductor cross section AWG	24 ... 12

Standards and Regulations

Designation	Air clearances and creepage distances
Standards/regulations	DIN EN 50178: 1998-04
Rated insulation voltage	230 V
Rated surge voltage	4 kV (1.2/50 μ s)
Insulation	Functional insulation
Pollution degree	2
Overvoltage category	III

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss

eCl@ss 10.0.1	27141152
---------------	----------

Interface module - UM 45-MKDS/MDSTBW/ 8SI/SO262 - 2319443

Classifications

eCl@ss

eCl@ss 4.0	27250300
eCl@ss 4.1	27250300
eCl@ss 5.0	27250300
eCl@ss 5.1	27250300
eCl@ss 6.0	27242600
eCl@ss 7.0	27141152
eCl@ss 8.0	27141152
eCl@ss 9.0	27141152

ETIM

ETIM 4.0	EC002780
ETIM 5.0	EC002780
ETIM 6.0	EC002780
ETIM 7.0	EC002780

UNSPSC

UNSPSC 6.01	30211824
UNSPSC 7.0901	39121421
UNSPSC 11	39121421
UNSPSC 12.01	39121421
UNSPSC 13.2	39121432
UNSPSC 18.0	39121432
UNSPSC 19.0	39121432
UNSPSC 20.0	39121432
UNSPSC 21.0	39121432