

## Starter kit - NLC-START-01 - 2701399

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



24 V DC base unit with NPN transistor outputs, LCD display, USB module, serial cable, input and output simulators and Quick Start Guide

### Product Description


Kit containing items required to start programming and testing the Nanoline family of controllers.

### Your advantages

- Operator panel
- Input simulator (available as 24 V AC or 24 V DC model)
- USB cable
- Basic unit
- Output simulator (available as 24 V AC or 24 V DC model)



### Key Commercial Data

Packing unit	1 pc
GTIN	 4 046356 325523
GTIN	4046356325523
Weight per Piece (excluding packing)	796.700 g
Custom tariff number	85371098
Country of origin	India

### Technical data

#### Environmental Product Compliance

	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50

## Starter kit - NLC-START-01 - 2701399

### Technical data

#### Environmental Product Compliance

	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"
--	-----------------------------------------------------------------------------------------------------

### Articles in set

#### Base unit - NLC-050-024D-06I-04QTN-00A - 2701030



24 V DC Nanoline base unit. Equipped with 6 digital input and 4 NPN digital output channels. Additional I/O channels can be added using a maximum of three I/O extension modules. Optional communication modules provide network or serial connectivity. Optional Operator Panel provides user interface. Programming is via nanoNavigator.

#### Operator terminal - NLC-OP1-LCD-032-4X20 - 2701137



User interface for Nanoline controllers. Mounts directly on the base unit. Can be mounted remotely using the mounting kit.

#### nanoLC module - NLC-MOD-USB - 2701195



Serial connection to PC's USB port for data transfer or software configuration

#### Cable - NLC-PC/USB-CBL 2M - 2701247



Cable, serial

## Starter kit - NLC-START-01 - 2701399

### Articles in set

Simulator card - NLC-050-24DC-IN-SIM - 2701357

Card to simulate inputs on an Nanoline base unit



Simulator card - NLC-050-24DC-OUT-SIM-T - 2701360

Card to simulate transistor outputs on a Nanoline base unit



### Classifications

#### eCl@ss

eCl@ss 4.0	27250300
eCl@ss 4.1	27250300
eCl@ss 5.0	27242700
eCl@ss 5.1	27242700
eCl@ss 6.0	27242200
eCl@ss 7.0	27242216
eCl@ss 8.0	27242216
eCl@ss 9.0	27242216

#### ETIM

ETIM 2.0	EC001417
ETIM 3.0	EC001417
ETIM 4.0	EC001417
ETIM 5.0	EC001417
ETIM 6.0	EC001417
ETIM 7.0	EC001417

#### UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	43172015

## Starter kit - NLC-START-01 - 2701399

### Classifications

#### UNSPSC

UNSPSC 12.01	43201404
UNSPSC 13.2	39122329
UNSPSC 18.0	39122329
UNSPSC 19.0	39122329
UNSPSC 20.0	39122329
UNSPSC 21.0	39122329