

## DIN rail bus connectors - ME 17,5 TBUS 1,5/ 5-ST-3,81 KM - 2713645

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




DIN rail connector, number of positions: 5, pitch: 3.81 mm, color: light gray

### Your advantages

- ✓ Space-saving DIN rail mounting
- ✓ Contact design enables electronics modules to be easily snapped on
- ✓ Power supply and communication without additional wiring
- ✓ Parallel and serial contacts for signal and data transmission



### Key Commercial Data

Packing unit	1 pc
GTIN	 4 017918 914509
GTIN	4017918914509
Weight per Piece (excluding packing)	4.930 g
Custom tariff number	85366990
Country of origin	Germany

### Technical data

#### Dimensions

Width	17.5 mm
Pitch	3.81 mm
Width [ w ]	17.5 mm
Height	7.5 mm

#### General

## DIN rail bus connectors - ME 17,5 TBUS 1,5/ 5-ST-3,81 KM - 2713645

### Technical data

#### General

Rated voltage (III/3)	125 V
Nominal current I <sub>N</sub>	8 A
Maximum load current	8 A
Insulating material	PA
Flammability rating according to UL 94	V0
Color	light gray
Number of positions	5

#### General product information

Type of note	Recommendation
Note	Material of contact pads for bus connector, galvanic gold (hard gold)

#### Standards and Regulations

Connection in acc. with standard	CUL
Flammability rating according to UL 94	V0

#### Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

### Classifications

#### eCl@ss

eCl@ss 4.0	27260700
eCl@ss 4.1	27260700
eCl@ss 5.0	27260700
eCl@ss 5.1	27260700
eCl@ss 6.0	27260700
eCl@ss 7.0	27440309
eCl@ss 8.0	27440309
eCl@ss 9.0	27440309

#### ETIM

ETIM 2.0	EC001031
ETIM 3.0	EC001031
ETIM 4.0	EC002638
ETIM 5.0	EC002638
ETIM 6.0	EC002638
ETIM 7.0	EC002638

# DIN rail bus connectors - ME 17,5 TBUS 1,5/ 5-ST-3,81 KM - 2713645

## Classifications

### UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	39121409

## Approvals


### Approvals


#### Approvals

UL Recognized / cUL Recognized / EAC / cULus Recognized

#### Ex Approvals

### Approval details

UL Recognized		<a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a>	E118976-20151204
Nominal voltage UN		150 V	
Nominal current IN		8 A	

cUL Recognized		<a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a>	E118976-20151204
Nominal voltage UN		150 V	
Nominal current IN		6 A	

EAC		B.01742
-----	---	---------

## DIN rail bus connectors - ME 17,5 TBUS 1,5/ 5-ST-3,81 KM - 2713645

### Approvals

cULus Recognized

