

## Surge protection device - C-UFB- 5DC/E 75 - 2763604

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Attachment plug with surge voltage coarse and fine protection, for coaxial signal interfaces with floating shield, signal voltage 5 V. Connection: BNC socket/plug

The illustration shows version C-UFB- 5DC/E

### Product Features

- Ground connection via separately led cable
- For insertion in the cable



### Key Commercial Data

|                                      |          |
|--------------------------------------|----------|
| Packing unit                         | 1 pc     |
| Weight per Piece (excluding packing) | 113.7 g  |
| Custom tariff number                 | 85363010 |
| Country of origin                    | Germany  |

### Technical data

#### Dimensions

|        |         |
|--------|---------|
| Height | 25.4 mm |
| Width  | 25.4 mm |
| Depth  | 93 mm   |

#### Ambient conditions

|                                 |                  |
|---------------------------------|------------------|
| Ambient temperature (operation) | -40 °C ... 80 °C |
| Degree of protection            | IP20             |

#### General

|   |            |
|---|------------|
| Housing material                                | Aluminum   |
| Color   | black      |
| Standards for clearances and creepage distances | VDE 0110-1 |

## Surge protection device - C-UFB- 5DC/E 75 - 2763604

### Technical data

#### General

|                     |   |
|---------------------|---|
|                     | IEC 60664-1                               |
| Mounting type       | Connection-specific intermediate plugging |
| Type                | Attachment plug                           |
| Direction of action | Line-Shield/Earth Ground                  |

#### Protective circuit

|   |  |
|---|--|
| IEC test classification   | C2                                     |
|   | C3                                     |
|   | D1                                     |
| Maximum continuous voltage $U_C$                                      | 5 V DC                                 |
| Maximum continuous voltage $U_C$ (wire-shield)                        | 5 V DC                                 |
| Nominal current $I_N$   | 185 mA (25 °C)                         |
| Operating effective current $I_C$ at $U_C$                            | $\leq 300 \mu\text{A}$                 |
| Residual current $I_{PE}$   | $\leq 2 \mu\text{A}$                   |
| Nominal discharge current $I_n$ (8/20) $\mu\text{s}$ (Core-Earth)     | 10 kA                                  |
| Nominal discharge current $I_n$ (8/20) $\mu\text{s}$ (Core-Shield)    | 10 kA                                  |
| Total surge current (8/20) $\mu\text{s}$                              | 20 kA                                  |
| Output voltage limitation at 1 kV/ $\mu\text{s}$ (Core-Earth) spike   | $\leq 500 \text{ V}$                   |
| Output voltage limitation at 1 kV/ $\mu\text{s}$ (Core-Shield) spike  | $\leq 35 \text{ V}$                    |
| Output voltage limitation at 1 kV/ $\mu\text{s}$ (Core-Shield) static | $\leq 15 \text{ V}$                    |
| Residual voltage at $I_n$ (conductor-shield)                          | $\leq 12 \text{ V}$                    |
| Voltage protection level $U_p$ (core-ground)                          | $\leq 500 \text{ V}$ (C1 - 1 kV/500 A) |
|   | $\leq 500 \text{ V}$ (C3 - 10 A)       |
| Voltage protection level $U_p$ (core-shield)                          | $\leq 55 \text{ V}$ (C1 - 1 kV/500 A)  |
|   | $\leq 25 \text{ V}$ (C3 - 10 A)        |
| Response time $t_A$ (Core-Earth)                                      | $\leq 100 \text{ ns}$                  |
| Response time $t_A$ (Core-GND)  | $\leq 500 \text{ ns}$                  |
| Input attenuation aE, asym.   | 1.3 dB ( $\leq 5 \text{ MHz}$ )        |
| Cut-off frequency $f_g$ (3 dB), asym. (shield) in 50 Ohm system       | typ. 80 MHz                            |
| Impulse durability (conductor-ground)                                 | C2 - 10 kV/5 kA                        |
|   | D1 - 2,5 kA                            |

#### Connection data

|                     |                 |
|---------------------|-----------------|
| Connection method   | BNC 75 $\Omega$ |
| Connection type IN  | BNC socket      |
| Connection type OUT | BNC plug        |

#### Connection, equipotential bonding

# Surge protection device - C-UFB- 5DC/E 75 - 2763604

## Technical data

### Connection, equipotential bonding

|                   |               |
|-------------------|---------------|
| Connection method | PVC litz wire |
|-------------------|---------------|

### Standards and Regulations

|                       |              |
|-----------------------|--------------|
| Standards/regulations | IEC 61643-21 |
|-----------------------|--------------|

## Classifications

### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27140201 |
| eCl@ss 4.1 | 27130801 |
| eCl@ss 5.0 | 27130801 |
| eCl@ss 5.1 | 27130801 |
| eCl@ss 6.0 | 27130807 |
| eCl@ss 7.0 | 27130807 |
| eCl@ss 8.0 | 27130807 |
| eCl@ss 9.0 | 27130807 |

### ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC000943 |
| ETIM 3.0 | EC000943 |
| ETIM 4.0 | EC000943 |
| ETIM 5.0 | EC000943 |

### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30212010 |
| UNSPSC 7.0901 | 39121610 |
| UNSPSC 11     | 39121610 |
| UNSPSC 12.01  | 39121610 |
| UNSPSC 13.2   | 39121620 |

## Approvals

### Approvals

---

Approvals

EAC / EAC

---

# Surge protection device - C-UFB- 5DC/E 75 - 2763604

## Approvals

Ex Approvals

---

Approvals submitted

## Approval details

EAC

EAC

## Drawings

Circuit diagram

