

Surge protection device - TT-UK5/ 48AC - 2794767

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Modular terminal block with surge voltage fine protection between clamping connector and DIN rail, nominal voltage: 48 V AC, for mounting on NS 32 or NS 35/7.5, terminal width: 6.2 mm, terminal height: 47 mm

The illustration shows version TT-UK5- 24 DC



Key Commercial Data

Packing unit	1 pc
Weight per Piece (excluding packing)	12.4 g
Custom tariff number	85363030
Country of origin	Greece

Technical data

Dimensions

Height	47 mm
Width	6.2 mm
Length	42.5 mm

Ambient conditions

Ambient temperature (operation)	-40 °C ... 85 °C
Degree of protection	IP20

General

Housing material	PA
Flammability rating according to UL 94	V2
Color	black
Mounting type	DIN rail/G-profile rail
Type	Single-level terminal block
Number of positions	1
Direction of action	Line-Earth Ground

Surge protection device - TT-UK5/ 48AC - 2794767

Technical data

Protective circuit

IEC test classification	C3
VDE requirement class	C3
Nominal voltage U_N	48 V AC
Maximum continuous voltage U_C	77 V DC
	55 V AC
Maximum continuous voltage U_C (wire-ground)	55 V AC
	77 V DC
Nominal current I_N	32 A (50 °C)
Residual current I_{PE}	$\leq 5 \mu\text{A}$
Nominal discharge current I_n (8/20) μs (Core-Earth)	62 A
Total surge current (8/20) μs	62 A
Max. discharge current I_{max} (8/20) μs maximum (Core-Earth)	62 A
Nominal pulse current I_{an} (10/1000) μs (Core-Earth)	12 A
Output voltage limitation at 1 kV/ μs (Core-Earth) static	$\leq 120 \text{ V}$
Residual voltage at I_n (conductor-ground)	$\leq 162 \text{ V}$
Response time t_A (Core-Earth)	$\leq 1 \text{ ns}$
Cut-off frequency f_g (3 dB), asym. (PE) in 150 Ohm system	typ. 2.9 MHz
Capacity (Core-Earth)	$\leq 0.63 \text{ nF}$
Impulse durability (conductor-ground)	C3 - 10 A

Connection data

Connection method	Screw connection
Connection type IN	Screw terminal blocks
Connection type OUT	Screw terminal blocks
Screw thread	M3
Tightening torque	0.5 Nm
Stripping length	8 mm
Conductor cross section flexible min.	0.2 mm ²
Conductor cross section flexible max.	4 mm ²
Conductor cross section solid min.	0.2 mm ²
Conductor cross section solid max.	4 mm ²
Conductor cross section AWG min.	24
Conductor cross section AWG max.	12

Standards and Regulations

Standards/regulations	IEC 61643-21
-----------------------	--------------

Surge protection device - TT-UK5/ 48AC - 2794767

Classifications

eCl@ss

eCl@ss 4.0	27140201
eCl@ss 4.1	27130801
eCl@ss 5.0	27130801
eCl@ss 5.1	27130801
eCl@ss 6.0	27130807
eCl@ss 7.0	27130807
eCl@ss 8.0	27130807
eCl@ss 9.0	27130807

ETIM

ETIM 2.0	EC000943
ETIM 3.0	EC000943
ETIM 4.0	EC000943
ETIM 5.0	EC000943

UNSPSC

UNSPSC 6.01	30212010
UNSPSC 7.0901	39121610
UNSPSC 11	39121610
UNSPSC 12.01	39121610
UNSPSC 13.2	39121620

Approvals

Approvals

Approvals

CSA / UL Recognized / cUL Recognized / EAC / cULus Recognized


Ex Approvals


Approvals submitted


Approval details

Surge protection device - TT-UK5/ 48AC - 2794767


Approvals

CSA 	
mm ² /AWG/kcmil	28-10
Nominal current I _N	34 A
Nominal voltage U _N	48 V

UL Recognized 	
mm ² /AWG/kcmil	26-10
Nominal current I _N	30 A
Nominal voltage U _N	48 V

cUL Recognized 	
mm ² /AWG/kcmil	26-10
Nominal current I _N	30 A
Nominal voltage U _N	48 V


EAC

cULus Recognized 
--

Drawings

Surge protection device - TT-UK5/ 48AC - 2794767

Circuit diagram



Schematic diagram

