

Plug-in module - LV-120-230AC/110DC - 2833738

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Plug-in module, for mounting on PR1 and PR2, with varistor and yellow LED, input voltage: 120 - 230 V AC/110 V DC \pm 20%

Product Features

- Mechanical coding to protect against mismatching
- Attenuation of reverse voltage induced in coil



Key Commercial Data

Packing unit	1 pc
Minimum order quantity	10 pc
Weight per Piece (excluding packing)	3.22 g
Custom tariff number	85366990
Country of origin	China

Technical data

General

Nominal voltage U_N	110 V DC
-----------------------	----------

Standards and Regulations

Connection in acc. with standard	CUL
----------------------------------	-----

Classifications

eCl@ss

eCl@ss 4.0	27371190
eCl@ss 4.1	27371190
eCl@ss 5.0	27371692
eCl@ss 5.1	27371692

Plug-in module - LV-120-230AC/110DC - 2833738

Classifications

eCl@ss

eCl@ss 6.0	27371603
eCl@ss 7.0	27371603
eCl@ss 8.0	27371010

ETIM

ETIM 2.0	EC001456
ETIM 3.0	EC001456
ETIM 4.0	EC001456
ETIM 5.0	EC000683

UNSPSC

UNSPSC 6.01	30211917
UNSPSC 7.0901	39121516
UNSPSC 11	39121516
UNSPSC 12.01	39121516
UNSPSC 13.2	39121516

Approvals

Approvals


Approvals

UL Recognized / cUL Recognized / EAC / cULus Recognized

Ex Approvals


Approvals submitted

Approval details


UL Recognized 

Plug-in module - LV-120-230AC/110DC - 2833738

Approvals

cUL Recognized 

EAC

cULus Recognized 

Drawings

Plug-in module - LV-120-230AC/110DC - 2833738

Circuit diagram

